Terahertz Band: The Last Piece of RF Spectrum Puzzle for Communication Systems

Hadeel Elayan, Osama Amin, Basem Shihada, Raed M. Shubair, and Mohamed-Slim Alouini

Abstract—Ultra-high bandwidth, negligible latency and seamless communication for devices and applications are envisioned as major milestones that will revolutionize the way by which societies create, distribute and consume information. The remarkable expansion of wireless data traffic that we are witnessing recently has advocated the investigation of suitable regimes in the radio spectrum to satisfy users' escalating requirements and allow the development and exploitation of both massive capacity and massive connectivity of heterogeneous infrastructures. To this end, the Terahertz (THz) frequency band (0.1-10 THz) has received noticeable attention in the research community as an ideal choice for scenarios involving high-speed transmission. Particularly, with the evolution of technologies and devices, advancements in THz communication is bridging the gap between the millimeter wave (mmW) and optical frequency ranges. Moreover, the IEEE 802.15 suite of standards has been issued to shape regulatory frameworks that will enable innovation and provide a complete solution that crosses between wired and wireless boundaries at 100 Gbps. Nonetheless, despite the expediting progress witnessed in THz wireless research, the THz band is still considered one of the least probed frequency bands. As such, in this work, we present an up-to-date review paper to analyze the fundamental elements and mechanisms associated with the THz system architecture. THz generation methods are first addressed by highlighting the recent progress in the electronics, photonics as well as plasmonics technology. To complement the devices, we introduce the recent channel models available for indoor, outdoor as well as nanoscale propagation at THz band frequencies. A comprehensive comparison is then presented between the THz wireless communication and its other contenders by treating in depth the limitations associated with each communication technology. In addition, several applications of THz wireless communication are discussed taking into account the various length scales at which such applications occur. Further, as standardization is a fundamental aspect in regulating wireless communication systems, we highlight the milestones achieved regarding THz standardization activities. Finally, a future outlook is provided by presenting and envisaging several potential use cases and attempts to guide the deployment of the THz frequency band and mitigate the challenges related to high frequency transmission.

Index Terms—Terahertz band, Terahertz communication, Terahertz transceivers, Terahertz channel model, high-speed transmission, Terahertz standardization.

H. Elayan is with the Department of Electrical and Computer Engineering, University of Toronto, ON M5S Canada (e-mail: hadeel.mohammad@mail.utoronto.ca)

O. Amin, B. Shihada and M.S. Alouini are with CEMSE Division, King Abdullah University of Science and Technology (KAUST), Thuwal, Makkah Province, Saudi Arabia. (e-mail: osama.amin, basem.shihada,slim.alouini@kaust.edu.sa)

R. M. Shubair is with the Research Laboratory of Electronics, Massachusetts Institute of Technology, Cambridge, MA 02139 USA (e-mail: rshubair@mit.edu).



1

Fig. 1. Wireless Roadmap Outlook up to the year 2035.

I. INTRODUCTION

The race towards improving human life via developing different technologies is witnessing a rapid pace in diverse fields and at various scales. As for the integrated circuit field, the race focuses on increasing the number of transistors on the wafer area, which is empirically predicted by Moore's Law [1]. In the case of the telecommunication sector, the race is moving towards boosting the data rate to fulfill different growing service requirements, which is anticipated by Edholm's law of bandwidth [2]. Wireless data traffic has been witnessing unprecedented expansion in the past few years. On the one hand, mobile data traffic is anticipated to boost sevenfold between 2016 and 2021. On the other hand, video traffic is foreseeing a threefold increase during the same time period [3]. Actually, the traffic of both wireless and mobile devices is predicted to represent 71% of the total traffic by 2022 [4]. In fact, by 2030, wireless data rates will be sufficient to compete with wired broadband [5] as demonstrated in Fig. 1. Such significant growth of wireless usage has led the research community to explore appropriate regions in the radio spectrum to satisfy the escalating needs of individuals. To this end, the Terahertz (THz) frequency band (0.1-10 THz) started to gain noticeable attention within the global community. Seamless data transfer, unlimited bandwidth, microsecond latency, and ultra-fast download are all features of the THz technology that is anticipated to revolutionize the telecommunications landscape and alter the route through which people communicate and access information.

The THz term has been first used within the microwave

society during the 1970s to describe the spectral frequency of interferometers, diode detectors coverage, and water laser resonance [6]–[8]. During the 2000s, the THz term was referred to as the submillimeter-wave with frequencies ranging between 100 GHz up to 10 THz. However, the boarder line between the submillimeter-waves and far infrared at that time was not clearly identified [9], [10]. The concept of utilizing the THz for ultra-broadband communication using non-line of sight (NLoS) signal components has been first proposed as a powerful solution for extremely high data rates in [11]. Since then, THz technology in general and communication in particular grasped the enthusiasm of the research community. This interest has been reflected in the increased number of publications issued in both IEEE and web of science in recent years as demonstrated in Fig. 2.



Fig. 2. Terahertz publications issued in both IEEE and web of science in recent years.

The THz frequency band assures extensive throughput, which theoretically extends up to several THz leading to capacities in the order of Terabits per second (Tbps) [12]. Such potential associated with THz technology attracted the broader research community. In fact, the combined efforts of active research groups is resulting in new designs, materials and fabrication methods that demonstrate endless opportunities for THz development. Table I presents examples of various groups that conduct THz research, which indicated that research in this area is executed in laboratories across the globe. Consequently, various funding agencies have been supporting THz projects and opening up new horizons in communications and devices deployed for beyond 5G technology. A detailed list of the most recent THz projects is demonstrated in Table II.

Several studies available in the literature reviewed and discussed the potential benefits that can be reaped from the THz band [9]. The first THz survey was introduced in 2002 by Siegel and focused on the sources, sensors and applications for frequencies higher than 500 GHz [9], [10], [13], [14]. During the same time period, another article has been issued in an attempt to demonstrate THz material characterization, which results in several applications including THz imaging and tomography [10]. From a medical and biological perspective, Siegel reviewed in [13] the developments observed in THz irradiation and sensing. In [14], Fitch and Osiander presented the first overview of THz technology for various practical deployments in communications and sensing including security

TABLE I
RESEARCH GROUPS WORKING ON THZ COMMUNICATION RELATED
TOPICS

Research Group/Lab	Location	R&D Activities
Mittleman Lab at Brown University.	USA	THz PHY layer, THz spec- troscopy, THz probes.
Broadband Wireless Net- working Lab at Georgia Institute of Technology.	USA	THz PHY layer, THz MAC layer, THz Nanocommunica- tion, THz devices.
NaNoNetworking Center in Catalunya.	Spain	THz Nanocommunication
Ultra-broadband Nano-Communication Laboratory at University at Buffalo.	USA	THz PHY layer, THz MAC layer, THz Nanocommunica- tion, THz devices.
Terahertz Electronics Lab- oratory at UCLA.	USA	THz sources, detectors, spectrometers, reconfigurable meta-films, imaging and spectroscopy.
MIT Terahertz Integrated Electronics Group	USA	Sensing, metrology, security and communication at THz fre- quencies.
Fraunhofer Institute for Applied Solid State Physics IAF	Germany	THz PHY layer, MAC layer and RF electronics.
Terahertz Communica- tions Lab	Germany	Channel investigation and Ter- ahertz reflectors.
Core technology labora- tory group in Nippon telegraph and telephone (NTT) corporation	Japan	Terahertz IC and Modulariza- tion Technology.
Texas Instrument Kilby Lab	USA	Ultra-Low Power Sub-THz CMOS Systems.
Tonouchi Lab at Osaka university	Japan	THz Nanoscience, THz Bio- science, THz-Bio sensing, and industrial applications.
THz Electronics Systems Lab at Korea University.	Korea	THz PHY layer, MAC layer and RF electronics.
Nanocommunications Center at Tampere University of Technology.	Finland	THz PHY layer, THz Nanocommunication.

and spectroscopy applications. After that, the promise brought by THz frequencies ranging from 100 GHz up to 30 THz has been demonstrated in [15], where discussions in terms of generation techniques and their correlated output power abilities have been presented. In [16], Jacob et al. provided a brief overview of the research activities including channel modeling and signal generation in both the millimeter wave (mmW) and THz bands. The first review on THz communication systems was presented in 2010, where Federici and Moeller presented a focused discussion on channel model basic considerations, THz generation methods and implementation issues of THz communications [17]. In [18], Kleine-Ostmann and Tadao Nagatsuma further expanded the discussion on the research progress in THz technology. In [19], Song and Nagatsuma shed the light on some advances of THz communication including achievable data rates and service distances in addition to highlighting the challenges associated with the 275 GHz up to 3 THz frequency band. A similar and brief review has

 TABLE II

 Examples of the Recent Funded THz Projects

Project Title	Funding Agency	Start Date	End Date	Fund	Objective
The Research and Development Project for Expansion of Radio Spectrum Re- sources.	The Ministry of information and communications in Japan, and the ministry of Education, Science, Sports and Culture.	2008	N/A	N/A	Developing technology for efficient frequency use, promoting shared fre- quency use, and encouraging a shift to use of higher frequencies.
Wireless Local Area Communication Systems at Terahertz Band.	Korea Government Funding Agency, IITA	2008	2012	25M \$	Developing wireless LAN/PAN systems based on electronic devices.
Semiconductor Nanodevices for Room Temperature THz Emission and Detec- tion (ROOTHz Project).	Framework Programmes for Research and Technological Development, European Union	2010	2013	2.1 M €	Fabricating solid state emitters and detectors at THz frequencies.
TERAPAN: Ultra-high Data rate trans- mission with steerable antennas at THz Frequencies.	German Federal Ministry of Education and Research	2013	2016	1.5M €	Demonstrating adaptive wireless point-to-point THz communication for indoor environments at data rates of up to 100 Gbps.
iBROW: Innovative ultra-BROadband ubiquitous Wireless communications through terahertz transceivers.	European Union's Horizon 2020 research and innovation program	2015	2018	4M €	Developing novel, low cost, energy- efficient and compact ultra-broadband short-range wireless communication transceiver technology.
TERAPOD: Terahertz based Ultra High Bandwidth Wireless Access Networks.	European Union's Horizon 2020 research and innovation program	2017	2020	3.47M €	Demonstrating THz wireless link within a data centre proof of concept deployment as well as investigating other use cases to beyond 5G.
ThoR: TeraHertz end-to-end wireless systems supporting ultra high data Rate applications.	European Union's Horizon 2020 research and innovation program, and the National Institute of Information and Communications Technology in Japan (NICT)	2018	2021	1.5M €	Providing technical solutions for the backhauling and fronthauling of traffic at the spectrum range near 300 GHz, which is able to cover data rates required for beyond 5G systems.
ULTRAWAVE: Ultra capacity wireless layer beyond 100 GHz based on mil- limeter wave Traveling Wave Tubes.	European Union's Horizon 2020 research and innovation program	2017	2020	3M €	Developing a high capacity backhaul that enables 5G cell densification by exploiting bands beyond 100 GHz.
TERRANOVA: Terabit/s Wireless Con- nectivity by TeraHertz innovative tech- nologies to deliver Optical Network Quality of Experience in Systems be- yond 5G.	European Union's Horizon 2020 research and innovation program	2017	2019	3M €	Providing reliable connectivity of high data rates and almost zero-latency in networks beyond 5G and extending the fiber optic systems to wireless.
EPIC: Enabling Practical Wireless Tb/s Communications with Next Generation Channel Coding.	European Union's Horizon 2020 research and innovation program	2017	2020	3M €	Developing new FEC codes to serve as an enabler of practicable beyond 5G wireless Tbps solutions.
DREAM: D-Band Radio solution En- abling up to 100 Gbps reconfigurable Approach for Meshed beyond 5G net- works.	European Union's Horizon 2020 research and innovation program	2017	2020	2.8M €	Enabling wireless links with data rate exceeding current V-band and E-band backhaul solutions to bring wireless systems to the speed of optical sys- tems.
WORTECS: Wireless Optical/Radio TErabit Communications.	European Union's Horizon 2020 research and innovation program	2017	2020	3M €	Exploring Tbps capability of above 90 GHz spectrum, while combining radio and optical wireless technologies.
TerraNova: An Integrated Testbed for True Terahertz Communications.	National Science Foundation (NSF)	2017	2019	750K \$	Developing the first integrated testbed specific to ultra-broadband communi- cation networks at THz frequencies.
EAGER: High-performance Optical- phonon-based Terahertz Sources Operating at Room Temperature.	National Science Foundation (NSF)	2017	2018	85K \$	Systematically exploring how to real- ize a new type of THz sources based on fundamentally different device op- eration principles.
Novel Terahertz Generators Based on magnetic Materials.	National Science Foundation (NSF)	2017	2020	210K \$	Creating a new type of THz gener- ators that are compact, inexpensive, and operate at room temperature by converting magnetic oscillations into THz waves.

been introduced by Nagatsuma in [20], which focused on demonstrations from 100 GHz to 300 GHz. In [21], Huang et al. provided both an overview of the state-of-the-art in THz wireless communication along with a tutorial for emerging applications in Terabit radio systems. In [22], Nagatsuma et al. reviewed the progress in photonics technology in generating THz signals ranging from 100 GHz to 300 GHz. In [23], Akyildiz et al. summarized the THz possible applications in wireless communications and defined the challenges of this promising band. In [24], Kürner and Priebe demonstrated more applications and reviewed briefly some research in THz communication. In [25], Hirata and Yaita discussed several THz technologies related to devices, circuits and antennas in addition to some recent experimental test-beds. In [26], Petrov et al. discussed further applications and defined major research challenges besides showcasing the progress towards THz standardization. In [27], Mumtaz et al. overviewed the opportunities and challenges in THz communications for vehicular networks indicating that communication at much higher frequencies is correlated with considerable potential when it comes to vehicular networks. In [28], Mittleman presented a perspective article where he highlighted several breakthroughs in the THz field which enabled new opportunities for both fundamental and applied research. The author emphasized on how the achievements of integrated THz sources and systems continue to accelerate enabling many new applications. In [29], Sengupta et al. reviewed the current progress in generating THz signals using electronics and hybrid electronics-photonics systems for communication, sensing and imaging applications. Recently, in [30], Chen et al. provided a literature review on the development towards THz communications and presented key technical challenges faced in THz wireless communication systems. In [31], from the Medium Access Protocol (MAC) perspective, Ghafoor et al. presented an in-depth survey of THz MAC protocols highlighting key features which should be considered while designing efficient protocols. In [32], Tekbiyik et al. addressed the current open issues in the design of THz wireless communication systems in terms of hardware, physical channel and network. Finally, in [33], Rappaport et al. presented a number of promising approaches and novel approaches that will aid in the development and implementation of the sixth generation (6G) of wireless networks using THz frequencies. The aforementioned review articles are listed in Table III, indicating clearly a high activity rate since the early time of 2000 as a result of the advances in both electronic and photonic technologies and the demand to fulfill several application requirements. To this end, there is still a demand to have a comprehensive view on the current progress and recent advances in this field that would help researchers draw futuristic steps for several communication systems. As such, this paper aims to serve such an objective by presenting the latest technologies associated with the THz frequency band.

Due to the rise of wireless traffic, the interest in higher bandwidth will never seem to descend before the capacity of the technology even beyond 5G has attained an upper bound [34]. In this paper, we shed the light on various opportunities associated with the deployment of the THz frequency band. These opportunities are demonstrated as applications that will facilitate a refined wireless experience coping with users' needs. Therefore, the main objective of the presented work is to provide the reader with an in-depth discussion, in which the authors summarize the latest literature findings regarding the fundamental aspects of THz frequency band wireless communication. The presented work will help researchers determine the gaps available in the literature paving the way for the research community to further develop research in the field. The rest of the paper is organized as follows. In Section II, we review the THz frequency band generation techniques available in the literature. In Section III, the THz channel models which capture the channel characteristics and propagation phenomena are presented. In Section IV, an extensive comparison is conducted in order to highlight the differences between THz wireless and other existing technologies including mmW, infrared, visible light and ultraviolet communication. In Section V, diverse applications which tackle nano, micro as well as macro-scale THz scenarios are presented. In Section VI, the standardization activities involved in regulating the usage of THz communication are extensively discussed. In Section VII, a plethora of opportunities brought by the deployment of the THz frequency band are demonstrated in an aim to effectively meet the needs of future networks and face the technical challenges associated with implementing THz communication. Finally, we conclude the paper in Section VIII.

II. TERAHERTZ FREQUENCY GENERATION METHODS

In recent years, broadband wireless links using the THz frequency band have been attracting the interests of research groups worldwide. By utilizing the frequency range above 100 GHz, the potential to employ extremely large bandwidths and achieve data rates exceeding 100 Gbps for radio communications will eventually be enabled. Nevertheless, in order to fulfill such aim, progress from the devices perspective is a necessity. In fact, the location of the THz band between the microwave and infrared frequency ranges imposes difficulty on signal generation and detection. Therefore, the frequency range between 0.1 and 10 THz has been often referred to as the THz Gap since the technologies used for generating and detecting such radiation is considered less mature. On the one hand, transistors and other quantum devices which rely on electron transport are limited to about 300 GHz. Devices functioning above these frequencies tend to be inefficient as semiconductor technologies fail to effectively convert electrical power into electromagnetic radiation at such range [35]. Operating at high frequencies requires rapidly alternating currents; thus, electrons will not be capable of travelling far enough to enable a device to work before the polarity of the voltage changes and the electrons change direction. On the other hand, the wavelength of photonic devices can be extended down to only 10 μ m (about 30 THz). This is due to the fact that electrons move vigorously between energy levels resulting in a difficulty to control the small discrete energy jumps needed to release photons with THz frequencies. Hence, designing optical systems with dimensions close to THz wavelengths is a challenge [36]. Nonetheless, with the development of novel techniques, often combining electronics and photonics

TABLE III	
TERAHERTZ TECHNOLOGY SURVEYS IN THE LITERATURE	

	Survey Title	Year Published	Survey Content	Reference
1	Terahertz Technology	2002	The first review article on the applications, sources and sensors for the THz technology with the em- phasis on frequencies higher than 500 GHz.	[9]
2	Materials for terahertz science and technology	2002	The article presents a review on material research in developing THz sources and detectors to support different applications.	[10]
3	Technology in Biology and Medicine	2004	The emerging field of THz is surveyed in biology and medicine, in which the irradiation and sensing capabilities of THz waves are applied for different applications.	[13]
4	Terahertz waves for communications and sensing	2004	This survey gives an overview of THz technology in terms of sources, detectors, and modulators needed for several applications such as security and spectroscopy.	[14]
5	Cutting-edge terahertz technology	2007	This review article gives an overview of the THz technology progress status and expected usages in wireless communication, agriculture and medical applications.	[15]
6	An Overview of Ongoing Activities in the Field of Channel Modeling, Spectrum Allocation and Standard- ization for mm-Wave and THz Indoor Communications	2009	An overview of mm-Wave and THz radio channel modeling along with some investigation results are presented. The article also discusses the status of standardization activities and plans.	[16]
7	Review of Terahertz and Subterahertz Wireless Com- munications	2010	The first review article on THz communication systems, which demonstrates basic channel model- ing, generation methods, detection, antennas, and a summary of THz communication link measure- ments.	[17]
8	A Review on Terahertz Communications Research	2011	A brief overview of emerging THz technologies, THz modulators, channel modeling and system research that might lead to future communication systems.	[18]
9	Present and Future of Terahertz Communications	2011	A review on THz communication as an alternative solution for high data rate future wireless commu- nication systems, especially short range networks.	[19]
10	Terahertz technologies: present and future	2011	This paper overviews the progress in THz tech- nology and applications as well as summarizes the recent demonstrations from 100 GHz to 300 GHz.	[20]
11	Terahertz Terabit Wireless Communication	2011	The state-of-the-art in THz wireless communica- tion along with the emerging applications in Terabit radio systems are demonstrated.	[21]
12	Terahertz wireless communications based on photonics technologies	2013	This paper overviews the recent advances in THz generation using phonetics towards achieving up to 100 Gbps data rate either on real time or offline.	[22]
13	Terahertz band: Next frontier for Wireless Communica- tions	2014	A review of THz applications and challenges in generation, channel modeling and communication systems is presented along with a brief discussion on experimental and simulation testbeds.	[23]
14	Towards THz Communications-status in research, stan- dardization and regulation	2014	The article provides an overview of THz commu- nications, research projects, spectrum regulations and ongoing standardization activities.	[24]
15	Ultrafast terahertz wireless communications technologies	2015	The article provides an overview of THz commu- nication research, development and implementation testbeds.	[25]
16	Terahertz Band Communications: Applications, Re- search Challenges, and Standardization Activities	2016	The article summarizes the recent achievements by industry, academia and standardization bodies in the THz field as well as discusses the open research challenges.	[26]
17	Terahertz Communication for Vehicular Networks	2017	An overview of the opportunities and challenges in THz communications for vehicular networks is provided.	[27]
18	Perspective: Terahertz science and technology	2017	The article discusses several breakthroughs in the THz field which enabled new opportunities for both fundamental and applied research.	[28]
19	Terahertz integrated electronic and hybrid elec- tronic-photonic systems	2018	The article reviews the development of THz in- tegrated electronic and hybrid electronic-photonic systems used in several applications.	[29]
20	A Survey on Terahertz Communications	2019	The paper provides a literature review on the devel- opment towards THz communications and presents some key technologies faced in THz wireless com- munication systems.	[30]
21	MAC Protocols for Terahertz Communication: A Com- prehensive Survey	2019	In this survey, detailed work on existing THz MAC protocols with classifications, band features, design issues and challenges are discussed.	[31]
22	Terahertz band communication systems: Challenges, novelties and standardization efforts	2019	The paper addresses the current open issues in the design of THz wireless communication system in terms of hardware, physical channel and network.	[32]
23	Wireless Communications and Applications Above 100 GHz: Opportunities and Challenges for 6G and Beyond	2019	The paper presents a number of promising ap- proaches that will aid in the development and implementation of the 6G wireless networks.	[33]

approaches, THz research is recently being pushed into the center stage. Fig. 3 presents a time-line of the progress in THz communication technology indicating how THz research is moving from an emerging to a more established field, where an obvious technological leap has been witnessed within the last decade. The following subsections discuss the latest THz advancements achieved focusing mainly on both the electronics and photonics fields while shedding the light on other techniques used to generate THz waves. In particular, Table V summarizes the advancements in THz technology by presenting the progress over the years in THz electronic as well as photonic transceivers, achievable data rates and propagating distances as well as output power.

A. Solid-State Electronics

Recent advances in the development of semiconductor components and their manufacturing technology are making THz systems both feasible and affordable resulting in compact devices. In fact, technology limitations have been overcome by architectural innovations as well as by new device structures.

1) Complementary Metal-Oxide-Semiconductor (CMOS): CMOS-based sources have been developing rapidly in recent years. Such technology possesses the advantages of high level integration, small form factor, and potential low cost. The high frequency operation ability of CMOS offers solutions in the lower band of the THz spectrum. This has been achieved by adding either a Voltage Controlled Oscillator (VCO) or inserting an active multiplier chain in the CMOS device [51]. Various triplers are used to multiply the frequency from a lower band to the THz frequency band by using nanoscale CMOS technology, where the consideration for CMOS THz circuits is enabled by technology scaling. In 2006, the scaling of a 65-nm CMOS process has resulted in a power gain frequency of 420 GHz, in which uni-axial strained silicon transistors with physical gate lengths of 29-nm have been used [52]. In 2007, a transistor cutoff frequency of 485 GHz [53] has been achieved while utilizing a 45-nm microprocessor technology. The authors in [54] demonstrated a 553 GHz quadruple-push oscillator using 45-nm CMOS technology, while in [55] the authors presented a 540 GHz signal generator fabricated in 40-nm bulk CMOS. In addition, the authors in [56] presented a 560 GHz frequency synthesizer realized in 65-nm CMOS technology. The chip configuration constituted of both a THz VCO along with a phase locked loop circuit. As such, it could be noticed that the constructive addition of harmonic signals allows devices to penetrate into hundreds of GHz range which indicates the impending THz era of CMOS technology. Such results states that the industry has been capable of keeping up with the documents reported by the International Roadmap for Semiconductors [57]. CMOS transmitters have actually achieved up to 105 Gbps data rate using a 40-nm CMOS process at 300 GHz [58].

2) Monolithic Microwave Integrated Circuits (MMIC): Assimilating a large number of tiny transistors into a small chip leads to circuits that are orders of magnitude smaller, cheaper, and faster than those built of discrete electronic components. Critical for reaching THz operational frequencies



Fig. 3. Time-line of Progress in Terahertz Communication Technology.

for integrated circuits are transistors with sufficiently high maximum oscillation frequency, f_{max} . The main approaches in developing high speed transistors include both transistor gate scaling for parasitic reduction as well as epitaxial material enhancement for improved electron transport properties. A variety of MMIC compatible processes include Heterojunction Bipolar Transistors (HBTs) and High Electron Mobility Transistors (HEMT). Both transistors use different semiconductor materials for the emitter and base regions, creating a heterojunction which limits the injection of holes from the base into the emitter. This allows high doping density to be used in the base which results in reducing the base resis-

tance while maintaining gain. In comparison to conventional bipolar transistors, HBTs have the advantage of higher cutoff frequency, higher voltage handling capability and reduced capacitive coupling with the substrate [59]. Materials used for the substrate include silicon, gallium arsenide (GaAs), and indium phosphide (InP). Both GaAs and InP HBTs are compatible for integration with 1.3-1.5 μ m optoelectronics such as lasers and photodetectors. In the case of HEMTs, the most commonly used material combination in the literature involves GaAs. Nonetheless, gallium nitride (GaN) HEMTs in recent years have attracted attention due to their highpower performance. GaN HEMT technology is promising for broadband wireless communication systems because of its high breakdown electric field and high saturation carrier velocity compared to other competing technologies such as GaAs and InP devices [60]. In fact, by utilizing a MMIC GaAs HEMT front-end, data rates up to 64 Gbps over 850 m [61] and 96 Gbps over 6 m [62] have been attained using a 240 GHz carrier frequency. In terms of InP-HEMT, improvement in electron-beam lithography is witnessing the increase in the speed of such devices as gate length decreases. A significant milestone was the first InP HEMT with $f_{\rm max} > 1$ THz reported in 2007 [63]. Further milestone achievements in amplifications at higher frequencies have been demonstrated with subsequent generation of transistors and designs at 480 GHz [64], 670 GHz [65], and 850 GHz [66]. By using 25-nm gate InP HEMT, $f_{\rm max}$ reached 1.5 THz [67]. Several devices with high $f_{\rm max}$ that operate around 1 THz are reported in Table IV.

Compared with CMOS, higher frequency sources with higher output powers have been obtained in the literature using HBT and HEMT technologies [68]. Nonetheless, CMOS still remains an attractive candidate for THz technology due to its lower cost and higher integration densities. It is to be noted that the development of physical principles of THz-wave amplification and oscillation is one of problems hindering progress in modern solid state electronics towards high frequencies. Therefore, novel perspectives are tied with use of resonant tunneling quantum effects, characterized by short transient times in comparison to the fast response of superconducting devices as will be discussed in the subsequent section.

TABLE IV PROGRESS OF INP HEMT IN RELATION TO OSCILLATION FREQUENCY AND GATE LENGTH

Gate Length	$\mathbf{f}_{\max}(\mathbf{THz})$	Reference
75 nm	0.91	[69]
75 nm	1.3	[70]
50 nm	1.1	[63]
50 nm	1.06	[71]
25 nm	1.5	[67]

3) Resonant Tunneling Diodes (RTD): A resonanttunneling diode (RTD) operates according to the tunneling principle, in which electrons pass through some resonant states at certain energy levels. RTD has been first demonstrated in 1974, where it consists of vertical stacking of nanometric epitaxial layers of semiconductor alloys forming a double barrier quantum well [72], which allows the RTD to exhibit a wideband negative differential conductance [73]. Over the last 10 years, progress has been achieved in increasing the output power of RTDs by almost two orders of magnitude and in extending the operation frequencies from earlier 0.7 THz to values near 2 THz [59]. Oscillations of RTDs in the microwave range were demonstrated at low temperature in 1984 [74] and the frequency was updated many times to several hundred GHz [75]. In 2010, a fundamental oscillation above 1 THz [76] have been attained. The oscillation frequency was further increased up to 1.42 THz using thin barriers and quantum wells [77]. Further, the authors in [78] and [79] indicated that reducing the length of the antenna integrated with the RTD extended the frequency up to 1.55 THz and 1.92 THz, respectively.

RTD oscillators are actually suitable for wireless data transmission because the output power is easily modulated by the bias voltage and oscillations can be controlled by either electrical or optical signals. Wireless data transmission with a data rate of 34 Gbps has been achieved in [80]. Because the size of RTD oscillators is small, it is possible to integrate multiple oscillators into one chip, which is convenient for multichannel transmissions Indeed, wireless transmissions using both frequency division multiplexing (FDM) and polarization division multiplexing (PDM) have been demonstrated in [81], in which data rates up to 56 Gbps were obtained. Yet, the drawback of this technology is that it cannot supply enough current for high power oscillations.

The technological progress that has been witnessed by the THz electronic devices is illustrated in Fig. 4, where the frequency of operation for CMOS, MMIC and RTD technologies is displayed versus power. It could also be concluded that in the cases where continued scaling of CMOS or integration with other silicon-based devices is inefficient, heterogeneous as well as tunneling devices are deployed. Nonetheless, despite the various progress that has been witnessed and is still ongoing in the field of solid state electronics, the drastic power decrement associated with this technology is a major bottleneck. Thereby, other technologies have been gaining considerable attention.

B. Photonics Technologies

THz devices based on electronic components possess both high resolution and high flexibility. Yet, for many applications, THz measurements for wideband and high speed signals are needed. Such requirement may not be implementable via electronic devices due to the limited speed and bandwidth. However, modern photonics, which have been widely used for wideband and high speed microwave measurements can provide broader bandwidths [108], [109]. In fact, the rise of THz wireless communication began as early as the year 2000 upon the initiation of a 120 GHz wireless link generated by photonic technologies [110]. The 120 GHz signal was the first commercial THz communication system with an allocated bandwidth of 18 GHz. A data rate of 10 Gbps has been attained with an on-off keying (OOK) modulation and 20 Gbps with a quadrature phase shift keying (QPSK) modulation [83], [84]. This achievement attracted broadcasters who aimed to transmit

 TABLE V

 PROGRESS IN THZ TECHNOLOGY, ACHIEVABLE DATA RATES AND PROPAGATION DISTANCE

Freq. (GHz)	Data Rate (Gbps)	Spectral Eff. (bps/Hz)	Distance (m)	Modulation Scehme	Power (dBm)	Technology	Reference	Year
100	200	-	0.5	QPSK	-10	Photodiode (PD)/ subharmonic mixer (SHM)	[82]	2013
120	10	0.59	5800	ASK and FEC	16	InGaAs/InP composite channel HEMT MMIC	[41]	2010
120	10	-	5800	ASK	16	UTC-PD /InP HEMT MMIC	[83]	2012
120	20	0.6	1700	QPSK	7	InP HEMT MMIC	[84]	2012
120	42/60	4.92/-	0.4	64QAM	-10	GaAs HEMT	[85]	2016
130	11	-	3	ASK	8.6	CMOS Transceiver Chipset	[86]	2015
140	2/10 real/non-real time	2.86	1500	16 QAM	-5	CMOS SHM/ Schottky barrier diodes	[87]	2013
144	48	-	1.8	QPSK/QAM	4	Direct conversion I/Q/ InP double HBT	[88]	2016
190	40/50	1/0.8	0.02/ 0.006	BPSK	-6	130 nm SiGe HBT	[88]	2017
200	75	-	0.002	QPSK	0	UTC-PD	[89]	2014
210	20	0.24	0.035	OOK	4.6	CMOS	[90]	2014
220	25	0.74	0.5	ASK	-3.4–1.4	active MMIC (50-nm mHEMT)	[91]	2011
240	30	-	40	QPSK/8PSK	-3.6	active MMIC components	[92]	2013
240	64/96	1/1.5	40	QPSK/PSK	-3.6	MMIC	[62]	2014
240	64	-	850	QPSK/8PSK	-3.6	MMIC	[61]	2015
300	24	0.24	0.5	ASK	-7	UTC-PD/ Schottky diode	[93]	2012
300	40	-	10	QPSK	-	Optical sub-harmonic IQ mixer	[94]	2015
300	64	1	1	QPSK	-4	MMIC	[95]	2015
330	50	-	0.5~1	ASK	-	UTC-PD/ Schottky diode detector	[96]	2015
340	3	2.86	50	16 QAM through 32 I/Q parallel channels	-17.5	CMOS SHM/ Schottky barrier diodes	[97]	2014
350-475	120	-	0.5	QPSK	-	UTC-PD/ Schottky mixer	[98]	2017
385	32	-	0.5	QPSK	-11	UTC-PD/SHM	[99]	2015
400	46	-	2	ASK	-16.5	UTC-PD/SHM	[100]	2014
400	60	-	0.5	QPSK	-17	UTC-PD/SHM	[101]	2015
434	10	-	-	ASK	-18.5	SiGe BiCMOS	[102]	2012
450	13	-	3.8	QPSK	-28	photomixer/PD	[103]	2018
450	18	-	3.8	PDM-QPSK	-28	photomixer/PD	[104]	2018
450	132	4.5	1.8	QAM	-28	UTC-PD/photomixer	[105]	2019
542	3	-	0.001	ASK	-6.7	RTD	[106]	2012
625	2.5	-	3	ASK	-14	Multiplier/SBD	[107]	2011



Fig. 4. Solid-state electronics frequency of operation versus power.

high-definition TV data [18] and demonstrated how photonic technologies played a key role in the development of firstage THz communication systems. Such achievement actually triggered the development of electronic devices and integrated circuits to strengthen the wireless technology. This eventually resulted in all electronic MMIC-based systems being successfully deployed in real-world events around the year 2008 [83]. Compared to solid-state electronics, photonic technologies not only improves the data rate but also fuses both fiber-optics and wireless networks. These devices have broadband characteristics, high modulation index as well as high-speed amplitude and/or phase coding introduced from optical coherent network technologies [111]. The most fundamental and widely used devices are based on the optical-to-THz or THz-to-optical conversion using interaction media such as nonlinear optical materials, photoconductors, and photodiodes. High speed THz wireless communication systems in the frequency range of 300 GHz-500 GHz, at data rates of 60 Gbps, 160 Gbps and up to 260 Gbps have been demonstrated in the literature indicating the potential of this technology [101], [112], [113].

1) Unitravelling Carrier Photodiode (UTC-PD): The evolution of photonics technology greatly increased the speed of signal processing systems. Photodiodes are examples of such devices that can provide both high speed and high saturation output resulting in the development of large-capacity communication systems. The combination of a high saturation power photodiode with an optical amplifier eliminates the postamplification electronics, extends the bandwidth, and simplifies the receiver configuration [114]. In particular, unitravelling carrier photodiodes (UTC-PD) [115] have a unique mode of operation which makes them promising candidates for such requirements. These photodiodes have been reported to have a 150 GHz bandwidth [116] and a high-saturation output current due to the reduced space charge effect in the depletion layer, which results from the high electron velocity [117]. Since the time UTC-PDs have been invented in 1997 [115], they have been used as photomixer chips. The frequency of the photomixer operation ranged from 75 to 170 GHz. Afterwards, the monolithic integration of a UTC-PD with planar antennas was reported and the operation frequency exceeded 1 THz in 2003 [118]. Upon antenna integration in UTC photomixers, operation frequencies exceeded 2 THz [117]. UTC-PDs also enable the use of travelling-wave designs [119], which provide slower frequency response roll-off, and are more compatible with integration. UTC-PDs with output powers of 148 μ W at 457 GHz and 24 μ W at 914 GHz have been approached [120]. In addition, a 160 Gbps THz wireless link has been achieved in the 300-500 GHz band using a single UTC-PD based transmitter as shown in [112].

2) Quantum Cascade Lasers (QCLs): A revolutionary advancement in THz technology arose in 2002 when successful operation of a quantum cascade laser (QCL) at THz frequencies has been reported in [121]. QCL basically bypasses semiconductor band-gap limitations in photonic devices by using sophisticated semiconductor heterostructure engineering and fabrication methods. The semiconductor layers are thin, thereby, very low energy transition happens when electron tunnel from one layer to the other. Due to the low energy, the emitted radiation occurs in the THz region. Since 2002, QCLs have quickly progressed in frequency coverage, increased power output, and increased operating temperature. Currently, they are the only sources capable of generating over 10 mW of coherent average power above 1 THz [122]. In order to characterize the high modulation speed capability of THz OCLs and build a high speed THz communication link, a fast detector is necessary. The authors in [123] demonstrated an all-photonic THz communication link at 3.8 THz by deploying QCL operating in pulse mode at the transmitter and a quantum well photodetector at the receiver. Later, the authors in [124] were capable of increasing the frequency to 4.1 THz by using a QCL which operates in continuous wave mode.

The progress witnessed in the photonics domain is a key enabler to the deployment of THz wireless links. Yet, the challenge remains in integrating these micrometer-scale bulky components of photonics into electronic chips. Surface plasmon-based circuits, which merge electronics and photonics at the nanoscale, may offer a solution to this sizecompatibility problem [125]. In plasmonics, waves do not rely on electrons or photons, but rather electromagnetic waves excite electrons at a surface of a metal and oscillate at optical frequencies. An advantage of these so-called surface plasmon polaritons (SPPs) is that they can be confined to an ultracompact area much smaller than an optical wavelength. In addition, SPPs oscillate at optical frequencies and thus can carry information at optical bandwidths. The efficient wave localization up to mid-infrared frequencies led plasmonics to become a promising alternative in future applications where both speed and size matters [126]. In particular, due to the two dimensional nature of the collective excitations, SPPs excited in graphene are confined much more strongly than those in conventional noble metals. The most important advantage of graphene would be the tunability of SPPs since the carrier densities in graphene can be easily controlled by electrical gating and doping. Therefore, graphene can be applied as THz metamaterial and can be tuned conveniently even for an encapsulated device [127]. Graphene-based THz compo-



Fig. 5. Terahertz Band Propagation Characteristics.

nents have actually shown very promising results in terms of generation, modulation as well as detection of THz waves [128] [129] [130]. Furthermore, various unique generation techniques have been recently proposed for THz waves. For instance, the authors in [131] experimentally demonstrated the generation of broadband THz waves from liquid water excited by femtosecond laser pulses. Their measurements showcased the significant dependence of the THz field on the relative position between the water film and the focal point of the laser beam. Compared with THz radiation generated from the air plasma, the THz radiation from liquid water has a distinct response to various optical pulse durations and shows linear energy dependence upon incident laser pulses. Such work will contribute to the exploration of laser-liquid interactions and their future as THz sources. Another example of original THz generation techniques involves the work demonstrated in [132]. The authors have shown that a dipole emitter can excite the resonances of a nanofiber and lead to strong electric and/or magnetic responses. They have experimentally demonstrated the magnetic dipole radiation enhancement for a structure containing a hole in a metallic screen and a dielectric subwavelength fiber. Their results are considered the first proof of concept of radiation enhancement of a magnetic dipole source in the vicinity of a subwavelength fiber. All these techniques will eventually result in breakthrough advancements in the various technological realms.

As indicated by Table V, a tradeoff between power, distance and data rate have to be achieved in order to choose the most applicable THz wireless communication scenario based on the user requirements. By varying the modulation schemes from the most simple amplitude shift keying (ASK) to PDM-QPSK as well as experimenting with different configurations of THzfiber integration, all electronics or all photonics systems, new opportunities are continuously developing for feasible THz wireless communication scenarios.

III. CHANNEL MODELING IN THE THZ FREQUENCY BAND

In order to realize an efficient wireless communication channel in the THz band, it is imperative to consider the various peculiarities which distinguishes such frequency range. In fact, the THz frequency band has high frequency attenuation [133], [136], distinctive reflective [137], [138] and scattering [139]–[141] properties as well as specular [142] and nonspecular [143] spatial distribution of the propagation paths. Moreover, the highly directive antenna radiation pattern used to overcome high path loss results in frequent misalignments of beams due to small scale mobility of user equipments [134]. The major propagation characteristics of THz waves are presented in Fig. 5. These effects cannot be neglected in the modeling process. As such, the existing channel models for the radio frequency (RF) band cannot be reused for the THz band as they do not capture various effects including the attenuation and noise introduced by molecular absorption, the scattering from particles which are comparable in size to the very small wavelength of THz waves, or the scintillation of THz radiation. Such features motivate the exploration of new models that efficiently characterize the THz spectrum. In our discussion of channel modeling in the THz frequency band, we will follow the classification illustrated in Fig. 6.

A. Outdoor Channel Models

Models that emulate THz channels in outdoor environments are scarce focusing only on point to point links. The first 120 GHz experimental radio station license has been provided by the Ministry of Internal Affairs and Communications of Japan in 2004, where the first outdoor transmission experiments over a distance of 170 m have been conducted [144]. These



Fig. 6. Terahertz Channel Model Classification.

experiments relied on utilizing mmW amplifiers along with high-gain antennas, such as the Gaussian optic lens antennas or the Cassegrain antennas, leading to a successful outdoor transmission experiment. Starting from 2007 onward, the 120 GHz wireless signals were generated using InP HEMT MMIC technologies accounting on the electronic systems advantages of compactness and low cost [145]. Upon the introduction of forward error correction (FEC) technologies, a 5.8 km 10 Gbps data transmission was achieved by increasing both the output power as well as antenna gain [41] [83]. The transmission data rate has been further increased to 22.2 Gbps by using the QPSK modulation scheme as shown in [84].

The current outdoor channel models tackle only point to point cases. This is because few cases exist in the literature where experimental measurements have been reported. In specific, for outdoor measurements, the interference from unintentional NLoS paths can limit the bit error rate (BER) performance [166]. For long distance wireless communications, THz links can suffer significant signal loss due to atmospheric weather effects as illustrated in Fig. 7. Yet, a closer look indicates that despite the existence of absorption peaks centered at specific frequencies, the availability of transmission windows allows establishing viable communication at the THz frequency band. Thus, it will be important to estimate the weather impact on high capacity data links and compare the performance degradation of THz links in comparison to other competing wireless approaches [167]. As the THz band channel is considered highly frequency selective, the transmission distance is limited by attenuation and the appropriate carrier frequency is determined according to the application. To be capable of developing THz outdoor channel models, the evaluation of link performance using realistic data streams is needed. In our opinion, a complete outdoor channel model could be attained by further exploring geometry-based, visibility-region based as well as map-based models which include parameterization from measurement campaign results. It must be emphasized that in order to operate in outdoor environments, certain measures have to be considered to avoid interference of passive services operating in the same band. Suitable frequency ranges are reported in Table VI based on studies conducted in [168], [169].



Fig. 7. The attenuation impact of different environmental effects at various frequencies [170].

 TABLE VI

 THz Frequency Ranges for Fixed Services [169]

Frequency Range (GHz)	Contiguous Band- width (GHz)	Loss (dB/km)
275-320	45	< 10
335-360	25	< 10
275-370	95	< 100
380-445	65	< 100
455-525	70	< 100
625-725	100	< 100
780-910	130	< 100

B. Indoor Channel Models

Unlike outdoor channel models, several indoor channel models are available in the literature. Indoor channel models can be categorized into either analytical or stochastic models. In terms of deterministic channels, the ray-tracing model is usually applied [135], [150]–[154]. This technique is sitespecific abiding with propagation theories and capturing the phenomenon of wave transmission with precision as it is based on geometrical optics, in which it is used for analyzing both the line of sight (LoS) and NLoS THz wave propagation paths.

Yet, the accuracy of the ray-tracing models depends heavily on the complete knowledge of material properties. This requires continuously adapting the model to a new environment, which can limit its time efficiency. From the communications perspective, it is fundamental to understand the large and smallscale statistics of the channel including path loss, shadowing and multipath propagation [155]. Hence, statistical methods arise as suitable options to model THz propagation based on empirical channel measurements. The first statistical model for THz channels, spanning the range between 275 and 325 GHz, has been provided in [156]. The given model depends on extensive ray-tracing simulations to realize the channel statistical parameters. Yet, the information concerning the channel statistics such as the correlation function and power-delay profile cannot be captured easily. To tackle such concerns, the authors in [157], [158] presented a geometrical statistical model for device-to-device (D2D) scatter channels at the sub-THz band. These models mimic the scattering and reflection patterns in a sub-THz D2D environment. It is important to note that since the reflecting and scattering properties are frequency-dependent in the THz band, statistical distributions and parameters for intra-cluster and inter-cluster need to be modeled properly. Therefore, a number of papers considered the characteristics of scattered multipath clusters including both angle and time of arrival for THz indoor channel modeling [159]–[161]. In addition, by investigating the blocking probability in order to describe the blocking effects of the propagation signals, the authors in [162] provided a modified THz channel model and proposed a path selection algorithm for finding the dominant signal. Similarly, in [171], the authors studied mean interference power and probability of outage in the THz band using stochastic geometry analysis. Further, the authors in [172] presented a time-domain channel model in the THz band, where the coherence bandwidth has been computed for both the entire THz band and its sub-bands. The demonstrated numerical evaluation along with the provided experimental results indicate that the obtained impulse response satisfies causality and show that knowledge of the variations in the coherence bandwidth allows the selection of the proper center frequency for wireless communications in the THz band. Unlike traditional channel measurements, scenariospecific models are also available in the literature. The authors in [163] presented a stochastic model for kiosk applications in the THz band, specifically between 220 and 340 GHz. A 3D ray-tracing simulator has been utilized to extract channel characteristics of three different kiosk application scenarios. Further, a stochastic channel model for future wireless THz data centers has been presented in [164]. The presented stochastic channel model accounts for the temporal and spatial dispersion of the propagation paths and enables fast generation of channel realizations. Both the RMS delay and angular spreads are employed as a validation of the model. In [165], another study on the statistical channel characterization of a THz scenario has been presented. This study deals with the frequency range between 240 and 300 GHz and is considered one of the first to provide single-sweep THz measurement results. The measured data enables finer temporal details to be attained aiding the design of reliable transceiver systems including antenna misalignment problems.

To achieve a balance between accuracy and efficiency, the authors in [173] suggested a hybrid channel model that combines both deterministic and statistical methods. In their discussion, the authors noted that a stochastic scatterer placement and ray-tracing hybrid approach could be developed. Scatterers in this case are stochastically placed, whereas the multipath propagation is traced and modeled based on ray-tracing techniques in a deterministic fashion. As such, geometry-based stochastic channel models are established. The advantage of following such mechanism includes the high modeling accuracy and the low complexity. On the one hand, the very rich multipath effects are included using statistical modeling. On the other hand, the critical multipath components are computed deterministically.

Furthermore, the authors in [174] provided an assessment for the communication system design requirements at higher frequencies. In fact, channel measurement results for 650 GHz carrier frequencies in comparison with 350 GHz carrier frequencies are given for a typical indoor environment. The authors presented an extensive multipath channel model which describes the spatial distribution of all available paths with their respective power levels. Thereby, a more established perception is provided for THz wave propagation at different wavelength ranges.

C. Nanoscale Channel Models

In the past few years, advancements in the field of nanotechnology have paved the way towards the development of miniaturized sensing devices which capitalize on the properties of novel nanomaterials. Such devices, denoted as nanodevices, can perform simple tasks including computing, data storing, sensing and actuation. As such, the formulation of nanonetworks will allow various applications in the biomedical, industrial, and military fields [175]. Based on radiative transfer theory and in light of molecular absorption, a physical channel model for wireless communication among nanodevices in the THz band is presented in [133]. The provided model considers the contribution from the different types and concentrations of molecules, where the HITRAN database is used in order to compute the attenuation that a wave suffers from. The Beer-Lambert law was used to compute the transmittance of the medium which relies on the medium absorption coefficient. The model provided in [133] was also utilized to compute the channel capacity of nanonetworks operating in the THz band, in which the authors deployed different power allocation schemes. The authors recommended using the lower end of the THz band which has lower absorption coefficients in order to ensure a strong received signal. Moreover, the sky noise model is the basis of the existing absorption noise models. The authors in [146] elaborated on this topic by presenting different perspectives on how to model the molecular absorption noise. However, there is no real experiments conducted in order to validate the proposed models. Not only absorption, but also scattering of molecules and small particles affects the propagation of electromagnetic waves. Hence, a wideband multiple scattering channel model for THz frequencies has

	TABLE VII	
WIRELESS	COMMUNICATION	CANDIDATES

Technology	Millimeter Wave	Terahertz	Infrared	Visible Light	Ultra-Violet
Data Rate	Up to 10 Gbps	Up to 100 Gbps	Up to 10 Gbps	Up to 10 Gbps	Few Gbps
Range	Short range	Short range – Medium range	Short range – long range	Short range	Short range
Power Consumption	Medium	Medium	Relatively low	Relatively low	Expected to be low
Network Topology	Point to Multi-point	Point to Multi-point	Point to Point	Point to Point	Point to Multi-point
Noise Source	Thermal noise	Thermal noise	Sun Light + Ambient Light	Sun Light + Ambient Light	Sun Light + Ambient Light
Weather Conditions	Robust	Robust	Sensitive	-	Sensitive
Security	Medium	High	High	High	To be determined

been demonstrated in [147]. Further, the authors in [148] presented an analytical model based on stochastic geometry for interference from omnidirectional nanosensors. However, in their model, they disregarded interference arising due to the existence of base stations. The authors in [149] tackled this issue where they studied interference from beamforming base stations. As such, it has been concluded that having a high density of base stations using beamforming with small beamwidth antennas and deploying a low density of nanosensors is recommended to improve the coverage probability.

IV. WILL THE TERAHERTZ BAND SURPASS ITS RIVALS ?

Carrier frequencies utilized for wireless communications have been increasing over the past years in an attempt to satisfy bandwidth requirements. While some of the interest of the research community is steered towards the mmW frequencies in an attempt to fulfill the demands of next generation wireless networks, another direction involves moving towards optical wireless communication to allow higher data rates, improve physical security and avoid electromagnetic interference. The optical wireless connectivity is permitted using infrared, visible, or ultraviolet sub-bands, offering a wide range performance of coverage and data rate [176]. To highlight the necessity of utilizing the THz frequency band and showcase its capability in comparison to other envisioned enablers of future wireless communication, we present through the following subsections a comprehensive study of the features of the different technologies as summarized in Table VII.

A. Millimeter Wave versus Terahertz

Millimetre-wave frequencies of 28, 60 as well 73 GHz can enable myriad applications to existing and emerging wireless networking deployments. Recent researches introduced mmW as a new frontier for wireless communication supporting multiple Gbps within a coverage of few meters. The mmW frequency range has been adopted by the Federal Communications Commission as the operational frequency of 5G technology. By designating more bandwidth, faster, higher-quality video, and multimedia content and services will continue to be delivered [177].

Despite the growing interest that arouse in mmW systems, the allocated bandwidth in such systems ranges from 7-9 GHz. This will eventually limit the total throughput of the channel to an insufficient level due to consumers' increasing demand. Moreover, to reach the envisioned data rate of 100 Gbps, transmission schemes must have a challenging spectral efficiency of 14 bps/Hz [24]. In addition, the capacity of the fronthaul/backhaul link needed to achieve few Gbps should be several times higher than the user data rate to guarantee reliable and timely data delivery from multiple users. Nonetheless, as the frequency increases up to the THz band, Tbps links could be attained with moderate, realistic spectral efficiencies of few bits per second per Hz. Operating at the THz frequency band also allows a higher link directionality in comparison to mmW at the same transmitter aperture since THz waves have less free-space diffraction due to its shorter wavelength compared to the mmW. Therefore, using small antennas with good directivity in THz communications reduces both the transmitted power and the signal interference between different antennas [178]. Another interesting feature is the lower eavesdropping chances in the THz band compared with the mmW. This is due to the high directionality of THz beams, which entail that unauthorized user(s) must be on the same narrow beamwidth to intercept messages.

B. Infrared versus Terahertz

One of the attractive, well-developed alternatives of radio frequency spectrum for wireless communication is the utilization of infrared radiation. The infrared technology uses laser transmitters with a wavelength span of 750-1600 nm that offer a cost-effective link with high data rates that could reach 10 Gbps. As such, it can provide a potential solution for the backhaul bottleneck [179]. The infrared transmissions also do not penetrate through walls or other opaque barriers, where they are confined to the room in which they originate. Such a feature secures the signal transmission against eavesdropping and precludes interference between links operating in different rooms. Nevertheless, as infrared radiation cannot penetrate walls, the installation of infrared access points that are interconnected via a wired backbone is required [180].

As part of the optical spectrum, infrared communication faces similar challenges that degrade its performance in different environments. For indoor environments, the ambient light signal sources, such as fluorescent lighting, induces noises at the receiver side. As for outdoor environments, in addition to moon/sun light noise level, atmospheric turbulence can limit the communication link availability and reliability, thus it is one of the main clogging factors of infrared communication deployment. The performance of optical links can be degraded even in clear weather as a result of scintillation, and temporary spatial variation of light intensity. Another major problem is the necessity of developing pointing, acquisition, and tracking (PAT) techniques, which are essential for operation due to the unguided narrow beam propagation through the free space. As a result, optical transceivers must be simultaneously pointed at each other for communication to take place, in which precise alignment should be maintained [181].

THz frequency band is a good candidate to replace the infrared communication under inconvenient weather conditions such as fog, dust and turbulence. Fig. 7 indicates that the THz band suffers lower attenuation due to fog compared to the infrared band. Recent experimental results showed that the atmospheric turbulence has a severe effect on the infrared signal, while it does not almost affect the THz signal. Moreover, the attenuation under the presence of cloud dust degrades the infrared channel but exhibits almost no measurable impact on the THz signal. As for the noise, THz systems are not affected by ambient optical signal sources. Due to the low level of photon energies at THz frequencies, the contribution to the total noise arises from the thermal one [170].

C. Visible Light versus Terahertz

Communication through visible light is a promising energyaware technology that has attracted people from both industry and academy to investigate its potential applications in different fields. Visible light communication (VLC) carries information by modulating light in the visible spectrum (390-750 nm) [182]. Recent advancements in lighting through light emitting diodes (LEDs) have enabled unprecedented energy efficiency and luminaire life span since LEDs can be pulsed at very high speeds without noticeable effect on the lighting output and human eye. LEDs also possess several attractive features including their low power consumption, small size, long life, low cost, and low heat radiation. Therefore, VLC can support a lot of vital services and application such as indoor localization, human-computer interaction, device-todevice communication, vehicular networks, traffic lights, and advertisement displays [176].

Despite the advantages associated with the deployment of VLC communication, several challenges exist that could hamper the effectiveness of the wireless communication link. In order to achieve high data rates in VLC links, a LoS channel should be primarily assumed in which both the transmitter and the receiver ought to have aligned field of views (FOV) to maximize the channel gain. Nevertheless, due to the receiver movement and continuous changes in orientation, the receivers' FOV cannot be always aligned with the transmitter. Such misalignment results in a significant drop in the received optical power [183]. In occasions where an object or a human blocks the LoS, a noticeable degradation of the optical power is witnessed resulting in severe data rate reduction. Similar to infrared waves, interference from ambient light can significantly reduce the received signal to oise ratio (SNR), degrading the communication quality [182]. Current research in visible light networking also sheds the light on downlink traffic without taking into consideration how the uplink can operate. Since a directional beam towards the receiver should be maintained in VLC uplink communication, significant throughput reductions when the mobile device is

constantly moving/rotating may occur. Thus, other wireless

technology should be used for transmitting uplink data [176]. Contrary to VLC systems, the THz frequency band permits NLoS propagation, which acts as a supplement when LoS is unavailable [23]. In such scenarios, NLoS propagation can be designed by strategically placing mounted dielectric mirrors to reflect the beam to the receiver. The resulting path loss is adequate due to the low reflection loss on dielectric mirrors. In fact, for distances up to 1 meter and a transmit power of 1 Watt, the capacity of only the NLoS component of a THz link is around 100 Gbps [152]. Furthermore, the THz frequency band is considered a candidate for uplink communication, a capability which VLC communication lacks. Another specific application where THz becomes a valuable solution is when there is a need to switch the lights off while looking for network service. Due to the restriction of positive and real signals, VLC systems will suffer from spectral efficiency loss. Indeed, utilizing unipolar OFDM system by imposing Hermitian symmetry characteristic leads to 3 dB performance loss in comparison to traditional bipolar systems that can be used in THz communication [184].

D. Ultra-Violet versus Terahertz

To relax the restrictions enforced by the PAT requirements of optical wireless communication, researchers investigated the optical wireless communication with NLoS capabilities. The deep ultra-violet (UV) band (200-280 nm) proves to be a natural candidate for short range NLoS communication, which is known also as optical scattering communication. In fact, since solar radiation is negligible at the ground level, the effect of background noise is insignificant, allowing the use of receivers with wide FOV. Thus, NLoS-UV can be used as an alternative to outdoor infrared or VLC links or in combination with existing optical and RF links as it is relatively robust to meteorological conditions [179].

Although UV communication possesses favorable features, it suffers from a number of shortcomings. For LoS links and despite the deployment of moderate FOV receivers, achievable ranges are still limited due to absorption by the ambient ozone. When operating under NLoS conditions for long ranges, the detrimental effects of fully coupled scattering as well as turbulence deteriorate the communication link. The effect of fading further impacts the received signal resulting in a distorted wave-front and fluctuating intensity. Therefore, data rates are limited to few Gbps and distances are restricted to short ranges [185].

Compared to UV links, the THz frequency band is considered a suitable contender. Unlike UV communication which imposes health restrictions and safety limits on both the eye



Fig. 8. Different ranges of Terahertz related applications.

and skin, an important point to emphasize is that the THz band is a non-ionization band; therefore, no health risks are associated with such frequencies [186]. From a communication perspective, this indicates that the THz data rates will not be vulnerable to any constraints. The fact that developing a UV system model suitable for practical application scenarios is still a demanding issue indicates that THz can compete UV communication in its anticipated applications.

V. TERAHERTZ APPLICATIONS

The THz band is envisioned as a potential candidate for a plethora of applications, which exist within the nano, micro as well as macro scales as illustrated in Fig. 8. Tbps data rates, reliable transmission and minimal latency [187] are among the multiple features that allow such band to support several scenarios in diverse domains.

A. Terahertz Nanoscale Applications

On a nanoscale and with the advent of the Internet of NanoThings (IoNT), the interconnection of various objects, sensors as well as devices results in ubiquitous networks tailored not only for device-to-device communication but also for extracting data from areas hard to access. Based on such technological progress, the communication architecture of nanonetworks has been established. These networks rely on the THz band to achieve communication between its different entities constituting of nanoscale transistors, processors as well as memories [188]. The interconnection of these pervasively deployed nanodevices with existing communication networks via the Internet creates a cyber physical system. Thus, nanoscale wireless communication is a key enabler of applications involving operations inside computers and devices for a typical range of few cm. These include chipto-chip, board-to-board and device-to-device communications. In addition, THz nanocells are envisioned to be part of the hierarchical cellular network for potential mobile users to support various indoor as well as outdoor applications [189]. Actually, almost all modern automation depends on nanoscale devices that can communicate with each other in order to provide smarter technical options. Hence, nanoscale communication is suited for applications in multimedia, security and defense, environment and industry as well as biomedical applications [190]. For example, THz nanosenors, detectors and cameras can support security applications through the capabilities that THz radiation possess which enables the detection of weapons, explosives as well as chemical and biological agents [191]. From an environmental perspective, THz nanosensors allows the detection of pollutants and as such renders the technology useful for food preservation and food processing applications. In terms of imaging, the THz band spectroscopic characteristics surpasses the currently available backscattering techniques and elucidates the dynamics of large biomolecules [192]. In addition, nanoantennas enable wireless interconnection amongst nanosensors deployed inside and over the human body resulting in many bio-nanosensing applications [193]. Several works exist pointing to the THz band as an enabler of in-vivo wireless nanosensor networks (iWNSNs) [194] [195]. In particular, the authors in [196] presented an attenuation model of intrabody THz propagation to facilitate the accurate design and practical deployment of iWNSNs. In subsequent studies, the authors also demonstrated both the photothermal impact [197] along with the noise effect [198] of THz intrabody communication to further verify the feasibility and prosperity of such propagation mechanism.

B. Terahertz Microscale Applications

THz wireless communication promises luring applications that meet consumer's demands of higher data rates especially at the micro-scale. Wireless local area network (WLAN) and wireless personal area network (WPAN) form the basis of such applications which include high-definition television (HDTV) in home distribution, wireless displays, seamless transfer of files, and THz access points in the areas with human congestion. The THz band provides small cell communication for mobile cellular networks, where ultra-high data rate can be provided to mobile users within transmission range up to 20 m. As such, THz frequencies provides transmission solutions in adhoc networks and for nomadic users by facilitating connection to access points including gates to the metro station, public building entrances, shopping malls, etc. In addition, microscale wireless communication at the THz band involves wireless transmission of uncompressed high definition (HD) videos for education, entertainment, telemedicine, as well as security purposes. The authors in [199] actually demonstrated the integration of a 4K camera into a THz communication link and showed the live streaming and recording of the uncompressed HD and 4K videos, followed by analysis of the link quality. The BER was measured at several link distances, where even at the maximum distance of 175 cm, the BER was below the FEC limit of 10^{-3} . Not only that, NHK (Japan broadcasting corporation) has already started trial experiments by telecasting 8K video using proprietary devices for Olympic games that will be held in 2020 [200]. Within the same scope, the new vision of modern railways signifies the need to interconnect infrastructure, trains and travelers. Therefore, to realize a seamless high data rate wireless connectivity, huge bandwidth is required. Such demand motivates the deployment of THz communications as they can offer orders of magnitude greater bandwidth than current spectrum allocations and enable very large antenna arrays which in turn provide high beamforming gains [201]. This facilitates relevant scenarios for railway applications including train to infrastructure, inter-wagon and intra-wagon communications. Further, kiosk downloading is another example of microscale application at THz frequencies, which offers ultra high downloads of digital information to users' handheld devices. For instance, Ad posters in metros, trains or streets can be the front interface for downloading pre-fixed contents such as newly released movie trailers, CDs, books, and magazines [189].

C. Terahertz Macroscale Applications

On a macroscale, THz wireless communication facilitates potential outdoor applications which range from few meters up to kilometers. For instance, wireless backhauling/fronthauling is one of the envisioned applications for the standard 100 Gbps transmission solutions [202]. In terms of backhauling, wireless point-to-point links are widely applied for transmission of information to the base stations of macrocells especially in those points where optic fiber is not available. In terms of fronthauling, wireless point-to-point links are those between the radio equipment controller of a base station and the remote radio head (radio unit). These systems are normally operating within the spectrum of 6 GHz to 80 GHz, in which they necessitate strict compliance with the LoS conditions between the transceivers of two nodes [203]. The increasing number of mobile and fixed users in both the private, industrial and service sectors will require hundreds of Gbps in the communication either to or between cell towers (backhaul) or between cell towers and remote radio heads (fronthaul). In such scenarios, apart from the high targeted data-rates (1 Tbps), the critical parameter is range, which should be in the order of some kilometers [187]. From the point of view of economic feasibility, the principal difference between the microwave solutions and the solutions for THz waves covers the price of spectrum, equipment costs and the difference in the time spent for assembly and on-site tuning. Future advancements which include massive deployment of small cells, implementation of cooperative multipoint transmission and Cloud Radio Access Networks (C-RAN) may increase the required data rates for either fronthauling or backhauling or both.

Wireless data centers are considered another promising application at the macroscale. Actually, the increasing call for cloud applications triggered competition between data centers in an attempt to supply users with an upgraded experience. This is accomplished by accommodating an extensive number of servers and providing adequate bandwidths to support many applications. In fact, wireless networking possess several features including the the adaptability and efficiency needed to provide possible ways to manage traffic bursts and finite network interfaces [204]. Nonetheless, wireless transmission capabilities are limited to short distances and intolerance to blockage leading to a deterioration in the efficiency of data centers if all wires are substituted. A better alternative exists through the augmentation of the data center network with wireless flyways rather than exchanging all cables [205]. The authors in [206] suggested using THz links in data centers as a parallel technology. Such deployment in data centers results in an enhanced performance experience along with immense savings in cable prices without compromising any throughput. The authors adopted a bandwidth of 120 GHz for data center applications, where atmospheric data has been utilized to model the THz channel.

VI. THZ STANDARDIZATION ACTIVITY

The work towards developing a powerful THz standard has launched during the last decade when the THz communication research was still in its infancy stage. In 2008, the IEEE 802.15 established the THz Interest Group as a milestone towards investigating the operation in the so called "no man's land" and specifically for frequency bands up to 3000 GHz. The new group conducted a liaison to the International Telecommunication Union (ITU) and the International Radio Amateur Union (IARU) regarding the description of the frequency bands higher than 275 GHz. Moreover, the group launched a call for contribution to cover different topics including possible THz applications, ways to realize transmitters and receivers, expected ranges and data rates, impact on regulations and market as well as ongoing research status. The journey of THz exploration started with studying the link budget for short distances considering the atmospheric attenuation for frequencies up to 2 THz. Despite the uncertainty in determining the realistic transmitted power, receiver sensitivity and thermal noise floor at this band, the study concluded the THz potential to deliver multi Gbps at an early time in 2008 [207]. Then, further solid analysis were conducted based on Shannon theory principles to prove the THz applicability for future in-home application with a data rate of 100 Gbps [208]. In addition, the THz interest group discussed the recent advances in research and lab measurements that encourage investigating the 300 GHz radio channel [209]. Specifically, detailed discussions about the current status of semiconductor technologies and photons based techniques for generation have been conducted in [210], [211] and [212], [213], respectively. Another important aspect that has been discussed is the desirable performance to the industry in addition to the cost and safety issues [214], [215].

In Nov. 2008, a science committee has been formed in order to bring the THz science communities together as a step to convert the THz interest group to a study group. To that end, the committee provided a comprehensive study on channel models, gave a general overview of technology trends and provided helpful technical feedback to ITU [216]. In March 2010, the THz interest group renewed the THz call for contributions to discuss the advances since the last call and further investigate the applicable modulation techniques, THz channel models, THz needed infrastructure and several other points [217]. In Nov. 2010, the interest group discussed the issues that will enable the THz communication deployment in order to prepare the agenda of the next ITU WRC that would be held in 2012 [217]. The discussion included defining spectrum bands for active services, where several bandwidths are defined with allowable attenuation for short distances. Moreover, the discussion showed the necessity to develop a holistic design approach which includes investigating channel characteristics by measurements, designing antennas to overcome the high attenuation, defining suitable communication systems, building an integrated RF front end and consider the connection to backbone network. In 2011, the THz interest group put more effort on investigating the existing THz generation technologies and the potential communication performance in addition to the expected road map in order to be discussed in WRC 2012 [218]-[220]. In March 2012, the interest group reviewed the results of WRC 2012 and the ITU radio regulations which allow the coexistence of active services beside passive services in the frequency band 275-1000 GHz. Specifically, the radio astronomy service occupies 275-323 GHz, 327-371 GHz, and 388-424 GHz, while the earth exploration-satellite and space research services operates in 275-277 GHz, 294-306 GHz and 316-334 GHz bands. The main issue in the discussion was about the necessary practical steps that should be adopted to prevent various active services (nomadic links, fixed links, airborne systems and multiple interferes) from interfering with the aforementioned passive services [221], [222]. The interest group discussed the prerequisites needed to start a study group, which included the participation of MAC expertise and people from industry in addition to the current PHY contributions [223].

Staring from 2013, the interest group added the MAC layer to its discussion sessions in order to investigate the requirements that should be fulfilled by the MAC protocols to accommodate for several THz communication applications [224]. A link level study is conducted via a simulation environment for THz communications using ray-tracing channel model [225]. Moreover, the data center operation and requirements have been discussed as a guide for future THz utilization for data center interconnection links [226]-[228]. Up until this stage of time, the IEEE 802.15 THz interest group activities included introducing a summary of THz technological developments, channel modeling and spectrum issues as well as working to generate a technical expectations document [229]. In July 2013, the THz interest group proposed starting a study group to explore the possibility of launching a standard towards 100 Gbps over beam switchable wireless point-to-point links, which can be used in wireless data center and backchaining. The inauguration of IEEE 802.15 study group 100G has been done in September 2013 [230]. The study group working tasks included discussing current technologies limits, investigating relevant PHY and MAC protocols, defining possible applications and introducing proposals for THz communication on wireless data centers [229].

In 2014, a group called "the task group 3d (TG3d)" has been initiated to adjust the 802.15.3 metrics in an aim to address100 Gbps for switched point-to-point links. Several applications are involved within this category including wireless data centers, backhauling/fronthauling as well as closeproximity communication such as kiosk downloading and D2D communication [231]. The first step towards defining bands for active services has been done when IEEE contacted the ITU to discuss allocating the THz band from 275 GHz to 325 GHz for mobile and fixed services. The "spectrum engineering techniques" ITU group confirmed also the availability of 23 GHz in the band 252-275 GHz for mobile and fixed services [169]. In addition, the WRC 2015 agreed to discuss the landmobile and fixed active services spectrum allocation in 275-450 GHz while maintaining protection of the passive services in the agenda of WRC 2019 [232]. To this end, the ITU-R is invited to identify technical and operational characteristics, study spectrum needs, develop propagation models, conduct sharing studies wit' the passive services and identify candidate frequency bands. Specifically, 8 groups namely: spectrum engineering techniques, propagation fundamentals, point-toarea propagation, point-to-point and earth space propagation, land mobile service, fixed services, space research, earth exploration-satellite service, and radio astronomy, are involved in conducting these studies [232]. The first standard of THz communication came to the scene in 2017, where it focused on point-to-point highly-directive links using 8 different channel bandwidths (as multiples of 2.16 GHz) [48]. Within the past two years, the interest group discussed several THz research activities such as multi-scale channel measurements, statistical channel characterization, solid state generation methods, antenna array designs, THz networks challenges and design, interference studies for THz intra-device communication systems and measurements of research data center.

VII. FUTURE RESEARCH DIRECTIONS

In this section, we shed the light on key enablers that will facilitate the progress and deployment of THz frequency links as well as open the door towards numerous applications that support both cellular as well as vehicular networks.

A. Terahertz Ultra-Massive MIMO

The THz frequency band is considered a key enabler in satisfying the continuously expanding demands of higher data rates. Yet, despite the huge bandwidth it provides, the band suffers from high atmospheric losses. Therefore, high-gain directional antennas are utilized in order to invoke communication over distances exceeding a few meters. Specifically, in the THz band, antennas become smaller and more elements can be installed in the same footprint. As such, stemmed from the Massive MIMO concept [233], the authors in [234] formulated an Ultra-Massive MIMO (UM-MIMO) channel. The concept of UM-MIMO relies on the adoption of ultra-dense frequency-tunable plasmonic nano-antenna arrays which are

TABLE VIII TIMELINE OF THZ STANDARDIZATION.

Jan. 2008 · · · · •	the IEEE 802.15 established the "THz Interest Group".
Mar. 2008	Call for contribution.
Nov. 2008 · · · · ·	Science committee formation.
Jul. 2009 · · · · •	Call for THz application.
Nov. 2011 · · · · ·	Call for THz application.
2012 · · · · •	THz applications and PHY layer issues discussion.
Sep. 2013 · · · · •	Inauguration of IEEE 802.15 study group 100G.
Dec. 2013 · · · · •	Study group 100G call for applications.
2014 · · · · •	Task group 3d (TG3d) formation.
2015-2016	Discussion with ITU about THz band allocation for mobile and fixed services.
Sep. 2017	IEEE Std 802.15.3d-2017 standard is approved as 100 Gbps wireless switched point-to-point system.

simultaneously utilized in transmission and reception thereby increasing the communication distance and, ultimately, the achievable data rates at THz frequencies [235]. Actually, the radiated signals may be regulated both in the elevation and the azimuth directions when securing two-dimensional or planar antenna arrays rather than one-dimensional or linear arrays. This results in 3D or Full-Dimension MIMO. The performance of UM-MIMO technology depends on two metrics, namely, the prospects of the plasmonic nanoantenna as well as the characteristics of the THz channel. As such, a channel model for the UM-MIMO systems using the array-of-subarray architecture has been proposed in [236]. The results indicate that when using 1024×1024 UM-MIMO systems at 0.3 THz and 1 THz, multi-Tbps links are achievable at distances of up to 20 m. Another important aspect is the dynamic resource allocation that can fully utilize the UM-MIMO system and gain the maximum benefits by adaptive design schemes [237]. Further, spatial modulation techniques that can influence the attributes of densely packed configurable nanoantenna subarrays have been studied by the authors in [238]. By using such an approach, both the capacity and spectral efficiency of the system are improved while maintaining acceptable beamforming performance. A particular spatial modulation configuration that establish good channel conditions is suggested based on the communication distance and the frequency of operation.

B. Terahertz Virtual Reality Perception via Cellular Networks

In order to attain a high-mobility automotive content streaming guarantee and guarantee an ultra reliable, low latency communication, it is essential to go well beyond what 5G can deliver. Although there are numerous compelling augmented reality and virtual reality applications, video is the most important and unique in its high bandwidth requirements. As such, the THz frequency band is sought as a technology that will provide both high capacity and dense coverage to bring these applications close to the end user. THz cellular networks will enable interactive, high dynamic range videos at increased resolutions and higher framerates, which actually necessitate 10 times the bit-rate required for 4K videos. THz transmission will help relieve any interference problem and provide extra data to support various instructions in video transmission. In addition, the THz band will be an enabler of 6 degrees of freedom (6DoF) videos providing users with an ability to move within and interact with the environment. Streaming live 6DoF content to deliver a "be there" experience is basically a forward-looking use case [239]. The results presented in [240] show that THz can deliver rates up to 16.4 Gbps with a delay threshold of 30 ms given that the impact of molecular absorption on the THz links, which considerably limits the communication range of the small base station, is relieved through network densification.

C. Terahertz Communications for Mobile HetNets

As the demands of communication services are developing in the direction of multiple users, large capacity and high speed mobile heterogeneous networks (HetNets), which combine various access network technologies, have become an imminent trend. As such, applying the THz technology to HetNets is a promising way to improve the transmission rate as well as the capacity and achieve a throughput at the level of Tbps [241]. Despite the high path loss and highly directional antenna requirements, these disadvantages could change into satisfactory features while operating in the femtocell regime. The deployment of femtocells reduces the required distance between both the active base-station and the user, while maintaining high signal to interference and noise ratio (SINR) at the receiver. Through such setup, femtocell base-stations improve the principle of frequency reuse and increase the capacity of the THz band systems. These access points are applied as portals to in-home service and automation, metro-stations, shopping malls, traffic lights and many other applications. As such, a novel era of communications via THz signals for mobile HetNets will be witnessed through the installation of these access points. Based on several metrics including the environment, the quality and type of communication service, both picocells and femtocells will be accordingly collocated within the macrocell footprint, as illustrated in Fig. 9. In fact, the authors in [242] note that 6G technology will allow cell-less architectures and compact integration of multiple frequencies and communication technologies. Such vision may be achieved by deploying multiple connectivity approaches and providing support for diverse and heterogeneous radios in the devices. Both seamless mobility support without overhead from handovers and QoS guarantees even in challenging mobility scenarios will be assured via the cell-less network procedures. In addition, since ultra-dense (UD)-HetNets are

bound to networks of big data, the authors in [243] introduced an AI-based network framework for energy-efficient operations. The presented framework supplies the network with the abilities of learning and inferring by analyzing the collected big data and then saving energy from both large scales (base station operation) and small scales (proactive caching and interference-aware resource allocation). The fact that THz communication is composed of access points in pervasive WiFi networks or base-station clustering in heterogenous networks, reinforcement learning may be deployed. Such self-organization capability is needed in THz communication to allow femtocells to autonomously recognize available spectrum and adjust their parameters subsequently. These cells will therefore operate under restrictions of avoiding intra/inter-tier interference and satisfy QoS requirements [244].



Fig. 9. Picocells and femtocells will be collocated within the macrocell footprint for THz wireless communication.

D. Terahertz 3D Beamforming Technology

One of the anticipated key enablers of THz wireless systems is 3D MIMO technology. In fact, real-world channels emphasize 3D characteristics leaving 2D MIMO techniques suboptimum [245]. 3D beamforming emerges as a solution to allow the construction of directional beams, extend the communication range as well as lower the interference level. Such technology holds a lot of promise to mitigate the unavoidable path loss experienced by the THz channel. In specific, the vertical beam pattern possesses a complete active correspondence per resource and per user equipment. 3D beamforming can also increase the strength of the signal by allowing the vertical main lobe to be located precisely at the receiver at any position. By adopting beam coordination or MIMO schemes, the alteration in vertical dimension has the potential to capitalize on additional diversity or spatial separation. This will lead to increasing the quality of the signal or increasing the number of supported users [246]. The ability to control the array's radiation pattern in 3D is nonetheless helpful to manipulate the multipath environment resulting in a constructive addition of the many signal components at the location of the expected receiver. On a similar frontier, the authors in [247] showcase tunable beam steering devices based on multilayer graphene-dielectric metamaterials. Since the effective refractive index of such metamaterials can be altered by changing the chemical potential of each graphene layer, the spatial distribution of the phase of the transmitted beam can be tailored. This results in establishing mechanisms for active beam steering resulting tunable transmitter/receiver modules for imaging and sensing at THz frequencies.

In addition, in order to mitigate the severe Doppler effect in mmW/THz massive MIMO systems, the authors in [248] proposed a beam division multiple access technique with per-beam synchronization capability in time and frequency. The authors verified via simulations the effectiveness of the proposed technique, where they showed that both the channel delay spread and Doppler frequency spread can be decreased via per-beam synchronization. This results in reducing the overall system overhead and outperforming conventional techniques in typical mobility scenarios.

E. Terahertz Communication for Urban Environments

In 2016, Facebook launched a new project called "Terragraph" to provide crowded urban areas with a high-speed internet service [249]. Terragraph adopted the mmW band, specifically the 60 GHz frequency range, and utilized distributed access points over the existing city infrastructure to allow quick, easy, low cost, and tractable installation. The multiple access points communicate with each other creating mesh network over the city instead of lying down optical fiber that is unfeasible in the high-density urban environments. The Terragraph introduced a powerful solution that uses 7-14 GHz bandwidth, which is considered the largest commercial radio band ever used till now. Moreover, it is a licensed free spectrum until this moment, which further decreases the mesh network deployment cost. Therefore, the Terragraph network introduced a good network connectivity solution to connect the service provider with end users via Gbps links using existing urban physical assets such as traffic light poles and lamps posts.

Despite the advantages mentioned above of the wireless mesh network solution, several obstacles can limit its performance and affect using it for similar scenarios in the future. First, the mmW frequency bands for the International Mobile Communications (IMT) 2020 are still under study, where the decision is expected to be taken in the World Radio Conference (WRC) 2019 that will be held on Nov. 2019 [250]. Second, the mmW band is expected to become crowded in the next decade. Thus, it will not be possible to accommodate more users and satisfy the exponential increase in population and data communications services. Finally, the mmW signal attenuates in the rain environment; thus the mesh network can be down under such circumstances. In other words, although the Terragraph project proposed rerouting techniques to avoid the scenario of link outage, rain can put most of the network in a blackout. As such, the THz frequency band provide a reliable wireless network access alternative with multiple backup links to avoid outages especially that it can work under different weather conditions. The THz band shall accommodate future population increase, urban environment rapid changes and new hungry rate services. An illustration of THz communication for urban environment is demonstrated in Fig. 10.

F. Terahertz Automotive Applications

1) Vehicle to Infrastructure Communication: The progress witnessed in the vehicle to infrastructure communication is



Fig. 10. THz wireless links as candidates for establishing communication in an urban environment.

considered a major milestone in the automotive industry. The initiation of a communication link that connects wireless between vehicles and the road-side infrastructures paves the way towards the the deployment of fully autonomous and smart transportation systems. According to the literature [251], the Long Term Evolution (LTE) has been the standard wireless interface which supports communications in vehicular environments. However, due to the stringent requirements of the users and the demands of the market in terms of higher data rates and lower latency to mobile users, new solutions must arise to fulfill the needs of next-generation networks. As such, the authors in [252] discussed the feasibility of establishing vehicle to infrastructure communications using higher frequencies, namely the mmW, to support automotive applications. Despite the anticipated benefits associated with mmW technology in both metropolitan and mobile highway scenarios, a number of challenges still arise. These include path-loss, shadowing, high directionality of beams as well as high sensitivity to blockage. Thereby, the THz frequency band seems to be a better alternative especially due to its capability of supporting the required estimated throughput of terabyte per driving hour [252]-[254]. A schematic diagram mimicking V2I communication using THz links is provided in Fig. 11. As such, the high data rate communication, highresolution radar sensing capabilities as well as the directional beam alignment capability of the THz transmitter and receiver result in such technology being a stronger candidate for smart vehicular communication scenarios.

Not only vehicle to infrastructure communication technology is evolving but also train to infrastructure (T2I) communication is developing towards smart rail mobility. Indeed, since high-data rate wireless connectivity with bandwidth beyond GHz is needed in order to establish T2I and interwagon scenarios, the authors in [255] demonstrated a complete study concerning measurement, simulation, and characterization of the T2I channel using the THz frequency band. Despite the high path loss of THz signals as well as the high mobility experienced by such high speed trains, the authors note that a robust THz link between the access points of the network can still be achieved. This is due to the fact that the user's desired content may be distributed into several segments that are delivered individually to broadcast points based on the train's schedule. Such procedure is facilitated by utilizing a proactive content caching scheme [256], paving the way towards seamless data transmission.



Fig. 11. Envisioned V2I future communication scenarios utilizing the THz frequency band.

2) Unmanned autonomous vehicles (UAVs): Unmanned autonomous vehicles (UAVs) have recently become accessible to the public. This resulted in several applications targeting both civilian and commercial domains. Typical examples involve weather monitoring, forest fire detection, traffic control, cargo transport, emergency search and rescue as well as communication relaying [257]. To deploy these applications, UAVs need to have a reliable communication link accessible at all times. For heights above 16 km, the effect of moisture is trivial; thus, THz attenuation is negligible. As such, THz can become a strong candidate to initiate reliable communications for varying UAV application scenarios.

In comparison to free space optical, the THz frequency band is a sufficient technology since it will not only enable high-capacity UAV-UAV wireless backhaul but also allow a better substitute in alleviating the high mobility environment of UAVs. In fact, as a result of mobility, communication links which suffer from the Doppler effect are minimized as carrier frequencies increase. Therefore, THz communication can establish high-speed communication links between two potentially dynamic locations [258]. UAVs also need shortdistance secure links to receive instructions or transmit data before dispersing to fulfill their remote controlled or autonomous missions. THz links are thereby considered a reliable venue for exchanging safety-critical information between UAVs as well as between the UAV and ground control stations. The large channel bandwidth of THz systems allows for specific protection measures against various standoff attacks like jamming and have the ability to completely hide information exchange. Furthermore, THz links could be also utilized between UAVs and airplanes in order to support internet for flights instead of using the satellite service. In this way, the UAV will act as a switchboard in the sky serving as an intermediary between the ground station and the airplane.

G. Terahertz Security Measures

Despite the prevailing expectation of enhanced security for wireless data links operating at high-frequencies, the authors in [259] show that an eavesdropper can intercept signals in LoS transmissions even when transmission occurs at high frequencies with narrow beams. The techniques the eavesdropper uses at high frequencies varies in comparison to those used for lower frequency transmissions. For high frequencies, an object is placed in the path of the transmission to scatter radiation towards the eavesdropper. Hence, the authors present a technique to mitigate such eavesdropping approach, which suggests characterizing the backscatter of the channel. If the signals incoming towards the transmitter can be measured and differentiated from the variable backscattered off mobile objects or the environment, then a sign of a probable attack would be through noticing any change, either an increase or a decrease, in the signal. Such technique provides an extra level of security especially when added to conventional countermeasures. Thus, to embed security into a directional wireless link, systems will necessitate original physical layer components and protocols for channel estimation. The presented work implies the significance of physical layer security in THz wireless networks and the urge for transceiver designs that include new counter-measures.

VIII. CONCLUSION

To satisfy the demands for higher data rates and support services of various traffic patterns, novel and efficient wireless technologies for a range of transmission links ought to be developed. As 5G networks are being deployed in various parts across the globe utilizing the mmW frequencies, the research community is exploring the THz frequency band as a revolutionary solution to support beyond 5G networks and enable applications that couldnt be deployed through 5G due to unforeseen difficulties. In this paper, a comprehensive survey has been presented for THz wireless communication in an attempt to review the devices, channel models as well as applications associated with the development of THz system architectures. As such, the THz frequency generation techniques have been extensively reviewed, where the progress in electronics, photonics as well as plasmonics techniques has been highlighted. Moreover, the THz channel models which capture the channel characteristics and propagation phenomena have been presented for different use-case scenarios. An extensive comparison was further conducted to point the differences between THz wireless and other existing technologies including mmW, infrared, visible light and ultraviolet communication indicating the foreseen potential upon the deployment of the THz band. In addition, a plethora of applications which tackle nano, micro as well as macro-scale THz scenarios have been demonstrated. Further, the standardization activities as well as the investigation efforts of frequency bands up to 3000 GHz are demonstrated indicating the collaborative efforts bringing THz science communities together. Finally, a number of promising techniques and deployment opportunities are presented in an attempt to efficiently satisfy the needs of future networks and face the technical challenges associated with implementing THz communication. Actually, with the continuous progress in THz devices, new foundations for rapid development of practical systems will be established. With the emergence of THz communication systems, societies will be expecting near-instant, unlimited wireless connectivity with capabilities extending beyond the 5G networks. Virtual reality, HD streaming as well as automation for the internet of things are amongst the many promising applications that shall be brought through the THz frequency band.

REFERENCES

- G. E. Moore, "Cramming more components onto integrated circuits," *Proc. IEEE*, vol. 86, no. 1, pp. 82–85, Jan. 1998.
- [2] S. Cherry, "Edholm's law of bandwidth," *IEEE Spectr.*, vol. 41, no. 7, pp. 58–60, July 2004.
- [3] C. V. N. Index, "Cisco visual networking index: Forecast and methodology 2015-2020," White paper, CISCO, 2015.
- [4] V. Cisco, "Cisco visual networking index: Forecast and trends, 2017–2022," White Paper, 2018.
- [5] R. Li, "Towards a new internet for the year 2030 and beyond," 2018.[6] A. J. Kerecman, "The Tungsten-P type Silicon point contact diode," in
- MTT-S Int. Microwave Symp. Dig. IEEE, 1973, pp. 30–34.
- [7] J. R. Ashley and F. Palka, "Transmission cavity and injection stabilization of an X-band transferred electron oscillator," in *MTT-S Int. Microwave Symp. Dig.* IEEE, 1973, pp. 181–182.
- [8] J. W. Fleming, "High-resolution submillimeter-wave Fourier-transform spectrometry of gases," *IEEE Trans. Microw. Theory Tech.*, vol. 22, no. 12, pp. 1023–1025, Dec. 1974.
- [9] P. H. Siegel, "Terahertz technology," *IEEE Trans. Microw. Theory Tech.*, vol. 50, no. 3, pp. 910–928, Mar. 2002.
- [10] B. Ferguson and X.-C. Zhang, "Materials for terahertz science and technology," *Nature materials*, vol. 1, no. 1, p. 26, Sep. 2002.
- [11] R. Piesiewicz, T. Kleine-Ostmann, N. Krumbholz, D. Mittleman, M. Koch, J. Schoebei, and T. Kurner, "Short-range ultra-broadband terahertz communications: Concepts and perspectives," *IEEE Antennas Propag. Mag.*, vol. 49, no. 6, pp. 24–39, Dec. 2007.
- [12] I. F. Akyildiz, J. M. Jornet, and C. Han, "TeraNets: ultra-broadband communication networks in the terahertz band," *IEEE Commun. Mag.*, vol. 21, no. 4, pp. 130–135, Aug. 2014.
- [13] P. H. Siegel, "Terahertz technology in biology and medicine," *IEEE Trans. Microw. Theory Tech.*, vol. 52, no. 10, pp. 2438–2447, Oct. 2004.
- [14] M. J. Fitch and R. Osiander, "Terahertz waves for communications and sensing," *Johns Hopkins APL technical digest*, vol. 25, no. 4, pp. 348–355, 2004.
- [15] M. Tonouchi, "Cutting-edge terahertz technology," Nature photon., vol. 1, no. 2, p. 97, 2007.
- [16] M. Jacob, S. Priebe, T. Kurner, C. Jastrow, T. Kleine-Ostmann, and T. Schrader, "An overview of ongoing activities in the field of channel modeling, spectrum allocation and standardization for mm-Wave and THz indoor communications," in *IEEE GLOBECOM Workshops*. IEEE, 2009, pp. 1–6.
- [17] J. Federici and L. Moeller, "Review of terahertz and subterahertz wireless communications," J. Appl. Phys., vol. 107, no. 11, p. 6, 2010.
- [18] T. Kleine-Ostmann and T. Nagatsuma, "A review on terahertz communications research," *J. Infrared Millim. Terahertz Waves*, vol. 32, no. 2, pp. 143–171, 2011.
- [19] H.-J. Song and T. Nagatsuma, "Present and future of terahertz communications," *IEEE Trans. THz Sci. Technol.*, vol. 1, no. 1, pp. 256–263, Sep. 2011.
- [20] T. Nagatsuma, "Terahertz technologies: present and future," IEICE Electron. Exp., vol. 8, no. 14, pp. 1127–1142, July 2011.
- [21] K.-C. Huang and Z. Wang, "Terahertz terabit wireless communication," *IEEE Microwave Magazine*, vol. 12, no. 4, pp. 108–116, 2011.
- [22] T. Nagatsuma, S. Horiguchi, Y. Minamikata, Y. Yoshimizu, S. Hisatake, S. Kuwano, N. Yoshimoto, J. Terada, and H. Takahashi, "Terahertz wireless communications based on photonics technologies," *Optics express*, vol. 21, no. 20, pp. 23736–23747, 2013.
- [23] I. F. Akyildiz, J. M. Jornet, and C. Han, "Terahertz band: Next frontier for wireless communications," *Physical Commun.*, vol. 12, pp. 16–32, Sep. 2014.

- [25] A. Hirata and M. Yaita, "Ultrafast terahertz wireless communications technologies," *IEEE Trans. THz Sci. Technol.*, vol. 5, no. 6, pp. 1128– 1132, Nov. 2015.
- [26] V. Petrov, A. Pyattaev, D. Moltchanov, and Y. Koucheryavy, "Terahertz band communications: Applications, research challenges, and standardization activities," in *Proc. 8th Intern. Congress Ultra Modern Telecommun. and Control Sys. and Workshops (ICUMT)*, Lisbon, Portugal, 2016, pp. 18–20.
- [27] S. Mumtaz, J. Miquel Jornet, J. Aulin, W. H. Gerstacker, X. Dong, and B. Ai, "Terahertz communication for vehicular networks," *IEEE Transactions on Vehicular Technology*, vol. 66, no. 7, pp. 5617–5625, July 2017.
- [28] D. M. Mittleman, "Perspective: Terahertz science and technology," *Journal of Applied Physics*, vol. 122, no. 23, p. 230901, 2017.
- [29] K. Sengupta, T. Nagatsuma, and D. M. Mittleman, "Terahertz integrated electronic and hybrid electronic–photonic systems," *Nature Electronics*, vol. 1, no. 12, p. 622, 2018.
- [30] Z. Chen, X. Ma, B. Zhang, Y. Zhang, Z. Niu, N. Kuang, W. Chen, L. Li, and S. Li, "A survey on terahertz communications," *China Communications*, vol. 16, no. 2, pp. 1–35, 2019.
- [31] S. Ghafoor, N. Boujnah, M. H. Rehmani, and A. Davy, "Mac protocols for terahertz communication: A comprehensive survey," *arXiv preprint* arXiv:1904.11441, 2019.
- [32] K. Tekbıyık, A. R. Ekti, G. K. Kurt, and A. Görçin, "Terahertz band communication systems: Challenges, novelties and standardization efforts," *Physical Communication*, 2019.
- [33] T. S. Rappaport, Y. Xing, O. Kanhere, S. Ju, A. Madanayake, S. Mandal, A. Alkhateeb, and G. C. Trichopoulos, "Wireless communications and applications above 100 GHz: Opportunities and challenges for 6g and beyond," *IEEE Access*, pp. 1–1, 2019. [Online]. Available: https://doi.org/10.1109/access.2019.2921522
- [34] H. Elayan, O. Amin, R. M. Shubair, and M.-S. Alouini, "Terahertz communication: The opportunities of wireless technology beyond 5G," in *International Conf. on Advanced Communication Technologies and Networking (CommNet).* IEEE, 2018, pp. 1–5.
- [35] Y. Zhu and S. Zhuang, "Ultrafast electromagnetic waves emitted from semiconductor," in *Behaviour of Electromagnetic Waves in Different Media and Structures*. IntechOpen, 2011.
- [36] M. Lee and M. C. Wanke, "Searching for a solid-state terahertz technology," *Science*, vol. 316, no. 5821, pp. 64–65, 2007.
- [37] T. Minotani, A. Hirata, and T. Nagatsuma, "A broadband 120-GHz Schottky-diode receiver for 10-Gbit/s wireless links," in *presented at the Asia Pacific Microw. Conf.*, 2002, Paper WE1A-5.
- [38] T. Kleine-Ostmann, K. Pierz, G. Hein, P. Dawson, and M. Koch, "Audio signal transmission over THz communication channel using semiconductor modulator," *Electron. Lett.*, vol. 40, no. 2, pp. 124–126, Jan. 2004.
- [39] C. Jastrow, K. Mu, R. Piesiewicz, T. Ku, M. Koch, T. Kleine-Ostmann et al., "300 GHz transmission system," *Electron. Lett.*, vol. 44, no. 3, pp. 213–214, Jan. 2008.
- [40] A. Hirata, "Transmission trial of television broadcast materials using 120-GHz-band wireless link," NTT Tech. Rev., vol. 7, no. 3, Mar 2009.
- [41] A. Hirata, T. Kosugi, H. Takahashi, J. Takeuchi, K. Murata, N. Kukutsu, Y. Kado, S. Okabe, T. Ikeda, F. Suginosita *et al.*, "5.8-km 10-Gbps data transmission over a 120-GHz-band wireless link," in *International Conf. on Wireless Information Technology and Systems (ICWITS)*. IEEE, 2010, pp. 1–4.
- [42] J.-D. Park, S. Kang, S. V. Thyagarajan, E. Alon, and A. M. Niknejad, "A 260 GHz fully integrated cmos transceiver for wireless chip-to-chip communication," in *Symposium on VLSI Circuits (VLSIC)*. IEEE, 2012, pp. 48–49.
- [43] H.-J. Song, K. Ajito, Y. Muramoto, A. Wakatsuki, T. Nagatsuma, and N. Kukutsu, "24 Gbit/s data transmission in 300 GHz band for future Terahertz communications," *Electron. Lett.*, vol. 48, no. 15, pp. 953– 954, 2012.
- [44] S. Koenig, D. Lopez-Diaz, J. Antes, F. Boes, R. Henneberger, A. Leuther, A. Tessmann, R. Schmogrow, D. Hillerkuss, R. Palmer et al., "Wireless sub-THz communication system with high data rate," *Nature Photon.*, vol. 7, no. 12, p. 977, 2013.
- [45] "1.25-km-long transmission experiment over 120-GHz-band FPU for SHV signal transmission, author=J. Tsumochi and F. Suginoshita and S. Okabe and H. Takeuchi and H. Takahashi and A. Hirata, booktitle=presented at the IEICE General Conf., year=2014, Paper C-2-111."

- [46] S. Kim, J. Yun, D. Yoon, M. Kim, J.-S. Rieh, M. Urteaga, and S. Jeon, "300 GHz integrated heterodyne receiver and transmitter with on-chip fundamental local oscillator and mixers," *IEEE Trans.THz Sci. and Technol.*, vol. 5, no. 1, pp. 92–101, 2014.
- [47] N. T. T. Corporation, "The world's-first compact transceiver for Terahertz wireless communication using the 300-GHz band with transmission rate of several-dozen Gigabits per second-was developed and experimentally demonstrated high-speed data transmission," *National Institute of Information and Communications Technology*, May, 26 2016. [Online]. Available: http://www.nict.go.jp/en/press/ 2016/05/26-1.html
- [48] T. Kürner, "THz communications-An overview and options for IEEE 802 standardization," IEEE 802.15-18-0516-02-0thz, Nov. 2018. [Online]. Available: https://mentor.ieee.org/802.15/documents\$? &\$is\$_\$group=0thz
- [49] H. Hamada, T. Fujimura, I. Abdo, K. Okada, H.-J. Song, H. Sugiyama, H. Matsuzaki, and H. Nosaka, "300-GHz. 100-Gb/s InP-HEMT wireless transceiver using a 300-GHz fundamental mixer," in *Proc. IEEE MTT-S Intern. Microwave Symp. (IMS)*. IEEE, 2018, pp. 1480–1483.
- [50] S. Lee, R. Dong, T. Yoshida, S. Amakawa, S. Hara, A. Kasamatsu, J. Sato, and M. Fujishima, "9.5 an 80Gb/s 300GHz-band single-chip cmos transceiver," in *International Solid-State Circuits Conf.-(ISSCC)*. IEEE, 2019, pp. 170–172.
- [51] S. Jameson and E. Socher, "A 0.3 THz radiating active ×27 frequency multiplier chain with 1 mw radiated power in CMOS 65-nm," *IEEE Trans.THz Sci. and Technol.*, vol. 5, no. 4, pp. 645–648, July 2015.
- [52] I. Post, M. Akbar, G. Curello, S. Gannavaram, W. Hafez, U. Jalan, K. Komeyli, J. Lin, N. Lindert, J. Park *et al.*, "A 65nm CMOS SOC technology featuring strained silicon transistors for RF applications," in *Electron Devices Meeting*, 2006. *IEDM'06. International*. IEEE, 2006, pp. 1–3.
- [53] S. Lee, B. Jagannathan, S. Narasimha, A. Chou, N. Zamdmer, J. Johnson, R. Williams, L. Wagner, J. Kim, J.-O. Plouchart *et al.*, "Record RF performance of 45-nm SOI CMOS technology," in *Electron Devices Meeting*, 2007. *IEDM 2007. IEEE International*. IEEE, 2007, pp. 255–258.
- [54] D. Shim, D. Koukis, D. J. Arenas, D. B. Tanner, and K. Kenneth, "553-GHz signal generation in CMOS using a quadruple-push oscillator," in *VLSI Circuits (VLSIC), 2011 Symposium on*. IEEE, 2011, pp. 154– 155.
- [55] W. Steyaert and P. Reynaert, "A 0.54 THz signal generator in 40 nm bulk CMOS with 22 GHz tuning range and integrated planar antenna," *IEEE J. Solid-State Circuits*, vol. 49, no. 7, pp. 1617–1626, July 2014.
- [56] Y. Zhao, Z.-Z. Chen, Y. Du, Y. Li, R. Al Hadi, G. Virbila, Y. Xu, Y. Kim, A. Tang, T. J. Reck *et al.*, "A 0.56 THz phase-locked frequency synthesizer in 65 nm CMOS technology," *IEEE J. Solid-State Circuits*, vol. 51, no. 12, pp. 3005–3019, 2016.
- [57] L. Wilson, "International technology roadmap for semiconductors (itrs)," *Semiconductor Industry Association*, 2011.
- [58] K. Takano, S. Amakawa, K. Katayama, S. Hara, R. Dong, A. Kasamatsu, I. Hosako, K. Mizuno, K. Takahashi, T. Yoshida, and M. Fujishima, "17.9 A 105Gb/s 300GHz CMOS transmitter," in 2017 IEEE International Solid-State Circuits Conf. (ISSCC), Feb. 2017, pp. 308–309.
- [59] P. A. Houston, "High-frequency heterojunction bipolar transistor device design and technology," *Electronics Communication Engineering Journal*, vol. 12, no. 5, pp. 220–228, Oct 2000.
- [60] S. Masuda, T. Ohki, K. Makiyama, M. Kanamura, N. Okamoto, H. Shigematsu, K. Imanishi, T. Kikkawa, K. Joshin, and N. Hara, "GaN MMIC amplifiers for W-band transceivers," in *Microwave Integrated Circuits Conf., 2009. EuMIC 2009. European.* IEEE, 2009, pp. 443– 446.
- [61] I. Kallfass, F. Boes, T. Messinger, J. Antes, A. Inam, U. Lewark, A. Tessmann, and R. Henneberger, "64 Gbit/s transmission over 850 m fixed wireless link at 240 GHz carrier frequency," *J. Infrared Millim. Terahertz Waves*, vol. 36, no. 2, pp. 221–233, 2015.
- [62] F. Boes, T. Messinger, J. Antes, D. Meier, A. Tessmann, A. Inam, and I. Kallfass, "Ultra-broadband MMIC-based wireless link at 240 GHz enabled by 64GS/s DAC," in 2014 39th International Conf. on Infrared, Millimeter, and Terahertz waves (IRMMW-THz), Sept 2014, pp. 1–2.
- [63] R. Lai, X. B. Mei, W. R. Deal, W. Yoshida, Y. M. Kim, P. H. Liu, J. Lee, J. Uyeda, V. Radisic, M. Lange, T. Gaier, L. Samoska, and A. Fung, "Sub 50 nm InP HEMT device with fmax greater than 1 THz," in 2007 IEEE International Electron Devices Meeting, Dec 2007, pp. 609–611.
- [64] W. Deal, X. Mei, V. Radisic, K. Leong, S. Sarkozy, B. Gorospe, J. Lee, P. Liu, W. Yoshida, J. Zhou *et al.*, "Demonstration of a 0.48 THz

amplifier module using InP HEMT transistors," *IEEE Microw. Wireless Compon. Lett.*, vol. 20, no. 5, pp. 289–291, 2010.

- [65] W. R. Deal, K. Leong, V. Radisic, S. Sarkozy, B. Gorospe, J. Lee, P. Liu, W. Yoshida, J. Zhou, M. Lange *et al.*, "Low noise amplification at 0.67 THz using 30 nm InP HEMTs," *IEEE Microw. Wireless Compon. Lett.*, vol. 21, no. 7, pp. 368–370, 2011.
- [66] W. Deal, K. Leong, A. Zamora, V. Radisic, and X. Mei, "Recent progress in scaling InP HEMT TMIC technology to 850 GHz," in *Microwave Symposium (IMS), 2014 IEEE MTT-S International*. IEEE, 2014, pp. 1–3.
- [67] X. Mei, W. Yoshida, M. Lange, J. Lee, J. Zhou, P.-H. Liu, K. Leong, A. Zamora, J. Padilla, S. Sarkozy *et al.*, "First demonstration of amplification at 1 THz using 25-nm InP high electron mobility transistor process," *IEEE Electron Device Lett.*, vol. 36, no. 4, pp. 327–329, 2015.
- [68] U. R. ETSI, "mmWave semiconductor industry technologies: Status and evolution," *white paper*, no. 15, 2016.
- [69] T. Takahashi, Y. Kawano, K. Makiyama, S. Shiba, M. Sato, Y. Nakasha, and N. Hara, "Enhancement of $f_{\rm max}$ to 910 GHz by adopting asymmetric gate recess and double-side-doped structure in 75-nm-gate InAlAs/InGaAs HEMTs," *IEEE Trans. on Electron Devices*, vol. 64, no. 1, pp. 89–95, Jan 2017.
- [70] —, "Maximum frequency of oscillation of 1.3 THz obtained by using an extended drain-side recess structure in 75-nm-gate InAlAs/InGaAs high-electron-mobility transistors," *Applied Physics Express*, vol. 10, no. 2, p. 024102, 2017.
- [71] D. H. Kim, J. A. del Alamo, P. Chen, W. Ha, M. Urteaga, and B. Brar, "50-nm E-mode In0.7Ga0.3As PHEMTs on 100-mm InP substrate with fmax > 1 THz," in 2010 International Electron Devices Meeting, Dec 2010, pp. 30.6.1–30.6.4.
- [72] L. Esaki and L. L. Chang, "New transport phenomenon in a semiconductor "superlattice"," *Phys. Rev. Lett.*, vol. 33, no. 8, p. 495, Aug. 1974.
- [73] K. H. Alharbi, "High performance terahertz resonant tunnelling diode sources and broadband antenna for air-side radiation," Ph.D. dissertation, University of Glasgow, 2016.
- [74] T. Sollner, P. Tannenwald, D. Peck, and W. Goodhue, "Quantum well oscillators," *Applied physics letters*, vol. 45, no. 12, pp. 1319–1321, 1984.
- [75] A. C. Beer, E. R. Weber, R. Willardson, R. A. Kiehl, and T. G. Sollner, *High Speed Heterostructure Devices*. Academic Press, 1994, vol. 41.
- [76] S. Suzuki, M. Asada, A. Teranishi, H. Sugiyama, and H. Yokoyama, "Fundamental oscillation of resonant tunneling diodes above 1 THz at room temperature," *Applied Physics Letters*, vol. 97, no. 24, p. 242102, 2010.
- [77] H. Kanaya, R. Sogabe, T. Maekawa, S. Suzuki, and M. Asada, "Fundamental oscillation up to 1.42 THz in resonant tunneling diodes by optimized collector spacer thickness," *J. Infrared Millim. Terahertz Waves*, vol. 35, no. 5, pp. 425–431, 2014.
- [78] T. Maekawa, H. Kanaya, S. Suzuki, and M. Asada, "Frequency increase in terahertz oscillation of resonant tunnelling diode up to 1.55 THz by reduced slot-antenna length," *Electronics Letters*, vol. 50, no. 17, pp. 1214–1216, 2014.
- [79] —, "Oscillation up to 1.92 THz in resonant tunneling diode by reduced conduction loss," *Applied Physics Express*, vol. 9, no. 2, p. 024101, 2016.
- [80] N. Oshima, K. Hashimoto, S. Suzuki, and M. Asada, "Wireless data transmission of 34 Gbit/s at a 500-GHz range using resonanttunnelling-diode terahertz oscillator," *Electronics Letters*, vol. 52, no. 22, pp. 1897–1898, 2016.
- [81] —, "Terahertz wireless data transmission with frequency and polarization division multiplexing using resonant-tunneling-diode oscillators," *IEEE Trans.THz Sci. and Technol.*, vol. 7, no. 5, pp. 593–598, 2017.
- [82] X. Li, J. Yu, J. Zhang, Z. Dong, F. Li, and N. Chi, "A 400G optical wireless integration delivery system," *Optics Express*, vol. 21, no. 16, pp. 18812–18819, 2013.
- [83] A. Hirata, T. Kosugi, H. Takahashi, J. Takeuchi, H. Togo, M. Yaita, N. Kukutsu, K. Aihara, K. Murata, Y. Sato *et al.*, "120-GHz-band wireless link technologies for outdoor 10-Gbit/s data transmission," *IEEE Trans. Microw. Theory Tech.*, vol. 60, no. 3, pp. 881–895, 2012.
- [84] H. Takahashi, A. Hirata, J. Takeuchi, N. Kukutsu, T. Kosugi, and K. Murata, "120-GHz-band 20-Gbit/s transmitter and receiver MMICs using quadrature phase shift keying," in *Microwave Integrated Circuits Conf. (EuMIC)*, 2012 7th European. IEEE, 2012, pp. 313–316.
- [85] I. Ando, M. Tanio, M. Ito, T. Kuwabara, T. Marumoto, and K. Kunihiro, "Wireless D-band communication up to 60 Gbit/s with 64QAM using

GaAs HEMT technology," in *Radio and Wireless Symposium (RWS)*, 2016 IEEE. IEEE, 2016, pp. 193–195.

- [86] M. Fujishima, S. Amakawa, K. Takano, K. Katayama, and T. Yoshida, "Tehrahertz CMOS design for low-power and high-speed wireless communication," *IEICE Trans. on Electronics*, vol. 98, no. 12, pp. 1091–1104, 2015.
- [87] C. Wang, C. Lin, Q. Chen, B. Lu, X. Deng, and J. Zhang, "A 10-Gbit/s wireless communication link using 16-QAM modulation in 140-GHz band," *IEEE Trans. on Microwave Theory and Techniques*, vol. 61, no. 7, pp. 2737–2746, 2013.
- [88] S. Carpenter, D. Nopchinda, M. Abbasi, Z. S. He, M. Bao, T. Eriksson, and H. Zirath, "A d-band 48-Gbit/s 64-QAM/QPSK direct-conversion I/Q transceiver chipset," *IEEE Trans. on Microwave Theory and Techniques*, vol. 64, no. 4, pp. 1285–1296, 2016.
- [89] H. Shams, M. J. Fice, K. Balakier, C. C. Renaud, F. van Dijk, and A. J. Seeds, "Photonic generation for multichannel THz wireless communication," *Optics express*, vol. 22, no. 19, pp. 23465–23472, 2014.
- [90] Z. Wang, P.-Y. Chiang, P. Nazari, C.-C. Wang, Z. Chen, and P. Heydari, "A CMOS 210-GHz fundamental transceiver with OOK modulation," *IEEE J. Solid-State Circuits*, vol. 49, no. 3, pp. 564–580, 2014.
- [91] I. Kallfass, J. Antes, T. Schneider, F. Kurz, D. Lopez-Diaz, S. Diebold, H. Massler, A. Leuther, and A. Tessmann, "All active MMIC-based wireless communication at 220 GHz," *IEEE Trans.THz Sci. and Technol.*, vol. 1, no. 2, pp. 477–487, Nov 2011.
- [92] J. Antes, S. Koenig, D. Lopez-Diaz, F. Boes, A. Tessmann, R. Henneberger, O. Ambacher, T. Zwick, and I. Kallfass, "Transmission of an 8-PSK modulated 30 Gbit/s signal using an MMIC-based 240 GHz wireless link," in 2013 IEEE MTT-S International Microwave Symposium Digest (MTT), June 2013, pp. 1–3.
- [93] H. J. Song, K. Ajito, Y. Muramoto, A. Wakatsuki, T. Nagatsuma, and N. Kukutsu, "24 Gbit/s data transmission in 300 GHz band for future terahertz communications," *Electronics Letters*, vol. 48, no. 15, pp. 953–954, July 2012.
- [94] A. Kanno, T. Kuri, I. Morohashi, I. Hosako, T. Kawanishi, Y. Yoshida, and K.-i. Kitayama, "Coherent terahertz wireless signal transmission using advanced optical fiber communication technology," *J. Infrared Millim. Terahertz Waves*, vol. 36, no. 2, pp. 180–197, 2015.
- [95] I. Kallfass, I. Dan, S. Rey, P. Harati, J. Antes, A. Tessmann, S. Wagner, M. Kuri, R. Weber, H. Massler *et al.*, "Towards MMIC-based 300GHz indoor wireless communication systems," *IEICE Trans. on Electronics*, vol. 98, no. 12, pp. 1081–1090, 2015.
- [96] T. Nagatsuma and G. Carpintero, "Recent progress and future prospect of photonics-enabled terahertz communications research," *IEICE Trans.* on *Electronics*, vol. 98, no. 12, pp. 1060–1070, 2015.
- [97] C. Wang, B. Lu, C. Lin, Q. Chen, L. Miao, X. Deng, and J. Zhang, "0.34-THz wireless link based on high-order modulation for future wireless local area network applications," *IEEE Trans.THz Sci. and Technol.*, vol. 4, no. 1, pp. 75–85, Jan 2014.
- [98] S. Jia, X. Yu, H. Hu, J. Yu, T. Morioka, P. U. Jepsen, and L. K. Oxenløwe, "120 Gb/s multi-channel THz wireless transmission and THz receiver performance analysis," *IEEE Photon. Technol. Lett.*, vol. 29, no. 3, pp. 310–313.
- [99] G. Ducournau, K. Engenhardt, P. Szriftgiser, D. Bacquet, M. Zaknoune, R. Kassi, E. Lecomte, and J.-F. Lampin, "32 Gbit/s QPSK transmission at 385 GHz using coherent fibre-optic technologies and THz double heterodyne detection," *Electronics Letters*, vol. 51, no. 12, pp. 915–917, 2015.
- [100] G. Ducournau, P. Szriftgiser, A. Beck, D. Bacquet, F. Pavanello, E. Peytavit, M. Zaknoune, T. Akalin, and J.-F. Lampin, "Ultrawidebandwidth single-channel 0.4-THz wireless link combining broadband quasi-optic photomixer and coherent detection," *IEEE Trans.THz Sci.* and Technol., vol. 4, no. 3, pp. 328–337, 2014.
- [101] X. Yu, R. Asif, M. Piels, D. Zibar, M. Galili, T. Morioka, P. U. Jepsen, and L. K. Oxenløwe, "60 Gbit/s 400 GHz wireless transmission," in *Photonics in Switching (PS), 2015 International Conf. on*. IEEE, 2015, pp. 4–6.
- [102] S. Hu, Y.-Z. Xiong, B. Zhang, L. Wang, T.-G. Lim, M. Je, and M. Madihian, "A SiGe BiCMOS transmitter/receiver chipset with onchip SIW antennas for terahertz applications," *IEEE J. Solid-State Circuits*, vol. 47, no. 11, pp. 2654–2664, 2012.
- [103] C. Wang, J. Yu, X. Li, P. Gou, and W. Zhou, "Fiber-THz-fiber link for THz signal transmission," *IEEE Photonics Journal*, vol. 10, no. 2, pp. 1–6, 2018.
- [104] C. Wang, X. Li, K. Wang, W. Zhou, and J. Yu, "Seamless integration of a fiber-THz wireless-fiber 2x2 MIMO broadband network," in *Asia Communications and Photonics Conf. (ACP)*. IEEE, 2018, pp. 1–3.

- [105] X. Li, J. Yu, L. Zhao, W. Zhou, K. Wang, M. Kong, G.-K. Chang, Y. Zhang, X. Pan, and X. Xin, "132-Gb/s photonics-aided singlecarrier wireless terahertz-wave signal transmission at 450GHz enabled by 64QAM modulation and probabilistic shaping," in *Optical Fiber Communication Conf.* Optical Society of America, 2019, pp. M4F-4.
- [106] K. Ishigaki, M. Shiraishi, S. Suzuki, M. Asada, N. Nishiyama, and S. Arai, "Direct intensity modulation and wireless data transmission characteristics of terahertz-oscillating resonant tunnelling diodes," *Electronics Letters*, vol. 48, no. 10, pp. 582–583, May 2012.
- [107] L. Moeller, J. Federici, and K. Su, "2.5 Gbit/s duobinary signalling with narrow bandwidth 0.625 terahertz source," *Electronics Letters*, vol. 47, no. 15, pp. 856–858, 2011.
- [108] J. Yao, "Microwave photonics," Journal of Lightwave Technology, vol. 27, no. 3, pp. 314–335, 2009.
- [109] R. A. Minasian, E. Chan, and X. Yi, "Microwave photonic signal processing," *Optics Express*, vol. 21, no. 19, pp. 22918–22936, 2013.
- [110] T. Nagatsuma, A. Hirata, Y. Royter, M. Shinagawa, T. Furuta, T. Ishibashi, and H. Ito, "A 120-GHz integrated photonic transmitter," in *Microwave Photonics, 2000. MWP 2000. International Topical Meeting on.* IEEE, 2000, pp. 225–228.
- [111] T. Nagatsuma, G. Ducournau, and C. C. Renaud, "Advances in terahertz communications accelerated by photonics," *Nature Photonics*, vol. 10, no. 6, p. 371, 2016.
- [112] X. Yu, S. Jia, H. Hu, M. Galili, T. Morioka, P. U. Jepsen, and L. K. Oxenløwe, "160 Gbit/s photonics wireless transmission in the 300-500 GHz band," *Apl Photonics*, vol. 1, no. 8, p. 081301, 2016.
- [113] X. Pang, S. Jia, O. Ozolins, X. Yu, H. Hu, L. Marcon, P. Guan, F. Da Ros, S. Popov, G. Jacobsen *et al.*, "260 Gbit/s photonic-wireless link in the THz band," in *Photonics Conf. (IPC)*, 2016 IEEE. IEEE, 2016, pp. 1–2.
- [114] Y. Miyamoto, M. Yoneyama, K. Hagimoto, T. Ishibashi, and N. Shimizu, "40 Gbit/s high sensitivity optical receiver with unitravelling-carrier photodiode acting as decision IC driver," *Electronics Letters*, vol. 34, no. 2, pp. 214–215, Jan 1998.
- [115] T. Ishibashi, N. Shimizu, S. Kodama, H. Ito, T. Nagatsuma, and T. Furuta, "Uni-traveling-carrier photodiodes," *tfil— Optoelectronics*, p. 83, 1997.
- [116] K. Sano, K. Murata, T. Akeyoshi, N. Shimizu, T. Otsuji, M. Yamamoto, T. Ishibashi, and E. Sano, "Ultra-fast optoelectronic circuit using resonant tunnelling diodes and unitravelling-carrier photodiode," *Electronics Letters*, vol. 34, no. 2, pp. 215–217, 1998.
- [117] T. Ishibashi, Y. Muramoto, T. Yoshimatsu, and H. Ito, "Unitravelingcarrier photodiodes for terahertz applications," *IEEE J. Sel. Topics Quantum Electron.*, vol. 20, no. 6, pp. 79–88, Nov 2014.
- [118] H. Ito, F. Nakajima, T. Furuta, K. Yoshino, Y. Hirota, and T. Ishibashi, "Photonic terahertz-wave generation using antenna-integrated unitravelling-carrier photodiode," *Electronics Letters*, vol. 39, no. 25, p. 1, 2003.
- [119] K. S. Giboney, J. Rodwell, and J. E. Bowers, "Traveling-wave photodetector theory," *IEEE Trans. on microwave theory and techniques*, vol. 45, no. 8, pp. 1310–1319, 1997.
- [120] C. Renaud, M. Robertson, D. Rogers, R. Firth, P. Cannard, R. Moore, and A. Seeds, "A high responsivity, broadband waveguide uni-travelling carrier photodiode," in *Millimeter-Wave and Terahertz Photonics*, vol. 6194. International Society for Optics and Photonics, 2006, p. 61940C.
- [121] R. Köhler, A. Tredicucci, F. Beltram, H. E. Beere, E. H. Linfield, A. G. Davies, D. A. Ritchie, R. C. Iotti, and F. Rossi, "Terahertz semiconductor-heterostructure laser," *Nature*, vol. 417, no. 6885, p. 156, 2002.
- [122] B. S. Williams, S. Kumar, Q. Hu, and J. L. Reno, "High-power terahertz quantum-cascade lasers," *Electronics letters*, vol. 42, no. 2, pp. 89–91, 2006.
- [123] P. D. Grant, S. R. Laframboise, R. Dudek, M. Graf, A. Bezinger, and H. C. Liu, "Terahertz free space communications demonstration with quantum cascade laser and quantum well photodetector," *Electronics Letters*, vol. 45, no. 18, pp. 952–954, August 2009.
- [124] Z. Chen, Z. Y. Tan, Y. J. Han, R. Zhang, X. G. Guo, H. Li, J. C. Cao, and H. C. Liu, "Wireless communication demonstration at 4.1 THz using quantum cascade laser and quantum well photodetector," *Electronics Letters*, vol. 47, no. 17, pp. 1002–1004, August 2011.
- [125] J. Leuthold, C. Hoessbacher, S. Muehlbrandt, A. Melikyan, M. Kohl, C. Koos, W. Freude, V. Dolores-Calzadilla, M. Smit, I. Suarez *et al.*, "Plasmonic communications: light on a wire," *Optics and Photonics News*, vol. 24, no. 5, pp. 28–35, 2013.
- [126] J. Leuthold, C. Haffner, W. Heni, C. Hoessbacher, J. Niegemann, Y. Fedoryshyn, A. Emboras, C. Hafner, A. Melikyan, M. Kohl, D. L. Elder, L. R. Dalton, and I. Tomkos, "Plasmonic devices for communications,"

in 17th International Conf. on Transparent Optical Networks (ICTON), July 2015, pp. 1–3.

- [127] X. Luo, T. Qiu, W. Lu, and Z. Ni, "Plasmons in graphene: recent progress and applications," *Materials Science and Engineering: R: Reports*, vol. 74, no. 11, pp. 351–376, 2013.
- [128] M. Hasan, S. Arezoomandan, H. Condori, and B. Sensale-Rodriguez, "Graphene terahertz devices for communications applications," *Nano Comm. Net.*, vol. 10, pp. 68–78, 2016.
- [129] J. M. Jornet and I. F. Akyildiz, "Graphene-based plasmonic nanoantenna for terahertz band communication in nanonetworks," *IEEE J. Sel. Areas Commun.*, vol. 31, no. 12, pp. 685–694, 2013.
- [130] H. Elayan, R. M. Shubair, and A. Kiourti, "On graphene-based THz plasmonic nano-antennas," in *16th Mediterranean Microwave Sympo*sium (MMS), Nov 2016, pp. 1–3.
- [131] Q. Jin, Y. E, K. Williams, J. Dai, and X.-C. Zhang, "Observation of broadband terahertz wave generation from liquid water," *Applied Physics Letters*, vol. 111, no. 7, p. 071103, 2017.
- [132] S. Atakaramians, I. V. Shadrivov, A. E. Miroshnichenko, A. Stefani, H. Ebendorff-Heidepriem, T. M. Monro, and S. Afshar V, "Enhanced terahertz magnetic dipole response by subwavelength fiber," *Apl Photonics*, vol. 3, no. 5, p. 051701, 2018.
- [133] J. M. Jornet and I. F. Akyildiz, "Channel modeling and capacity analysis for electromagnetic wireless nanonetworks in the terahertz band," *IEEE Trans. Commun.*, vol. 10, no. 10, pp. 3211–3221, Oct. 2011.
- [134] V. Petrov, D. Moltchanov, Y. Koucheryavy, and J. M. Jornet, "The effect of small-scale mobility on terahertz band communications," in *Proceedings of the 5th ACM International Conf. on Nanoscale Computing and Communication.* ACM, 2018, p. 40.
- [135] C. Han, A. O. Bicen, and I. F. Akyildiz, "Multi-ray channel modeling and wideband characterization for wireless communications in the terahertz band," *IEEE Trans. Commun.*, vol. 14, no. 5, pp. 2402–2412, May 2015.
- [136] I. E. Gordon, L. S. Rothman, C. Hill, R. V. Kochanov, Y. Tan, P. F. Bernath, M. Birk, V. Boudon, A. Campargue, K. Chance *et al.*, "The HITRAN2016 molecular spectroscopic database," *Journal of Quantitative Spectroscopy and Radiative Transfer*, vol. 203, pp. 3–69, 2017.
- [137] S. K. Nayar, K. Ikeuchi, and T. Kanade, "Surface reflection: physical and geometrical perspectives," *IEEE Trans. on Pattern Analysis & Machine Intelligence*, no. 7, pp. 611–634, 1991.
- [138] C. Jansen, R. Piesiewicz, D. Mittleman, T. Kurner, and M. Koch, "The impact of reflections from stratified building materials on the wave propagation in future indoor terahertz communication systems," *IEEE Trans. Antennas Propag.*, vol. 56, no. 5, pp. 1413–1419, 2008.
- [139] R. Piesiewicz, C. Jansen, D. Mittleman, T. Kleine-Ostmann, M. Koch, and T. Kurner, "Scattering analysis for the modeling of THz communication systems," *IEEE Trans. Antennas Propag.*
- [140] —, "Scattering analysis for the modeling of THz communication systems," *IEEE Trans. Antennas Propag.*, vol. 55, no. 11, pp. 3002– 3009, Nov 2007.
- [141] C. Jansen, S. Priebe, C. Moller, M. Jacob, H. Dierke, M. Koch, and T. Kurner, "Diffuse scattering from rough surfaces in THz communication channels," *IEEE Trans.THz Sci. and Technol.*, vol. 1, no. 2, pp. 462–472, 2011.
- [142] H. Xu, V. Kukshya, and T. S. Rappaport, "Spatial and temporal characteristics of 60-GHz indoor channels," *IEEE J. Sel. Areas Commun.*, vol. 20, no. 3, pp. 620–630, 2002.
- [143] S. Priebe, M. Jacob, C. Jansen, and T. Kürner, "Non-specular scattering modeling for THz propagation simulations," in *Proceedings of the 5th European Conf. on Antennas and Propagation (EUCAP)*. IEEE, 2011, pp. 1–5.
- [144] A. Hirata, T. Kosugi, N. Meisl, T. Shibata, and T. Nagatsuma, "Highdirectivity photonic emitter using photodiode module integrated with HEMT amplifier for 10-Gbit/s wireless link," *IEEE Trans. Microw. Theory Tech.*, vol. 52, no. 8, pp. 1843–1850, 2004.
- [145] A. Hirata, R. Yamaguchi, T. Kosugi, H. Takahashi, K. Murata, T. Nagatsuma, N. Kukutsu, Y. Kado, N. Iai, S. Okabe *et al.*, "10-Gbit/s wireless link using InP HEMT MMICs for generating 120-GHz-band millimeter-wave signal," *IEEE Trans. Microw. Theory Tech.*, vol. 57, no. 5, pp. 1102–1109, 2009.
- [146] J. Kokkoniemi, J. Lehtomäki, and M. Juntti, "A discussion on molecular absorption noise in the terahertz band," *Nano Communication Networks*, vol. 8, pp. 35–45, 2016.
- [147] J. Kokkoniemi, J. Lehtomäki, K. Umebayashi, and M. Juntti, "Frequency and time domain channel models for nanonetworks in terahertz

band," *IEEE Trans. on Antennas and Propagation*, vol. 63, no. 2, pp. 678–691, 2015.

- [148] V. Petrov, D. Moltchanov, and Y. Koucheryavy, "Interference and SINR in dense terahertz networks," in 82nd Vehicular Technology Conf. (VTC Fall). IEEE, 2015, pp. 1–5.
- [149] C.-C. Wang, X.-W. Yao, C. Han, and W.-L. Wang, "Interference and coverage analysis for terahertz band communication in nanonetworks," in *Global Communications Conf.*, 2017. IEEE, 2017, pp. 1–6.
- [150] S. Priebe, M. Jacob, and T. Kürner, "Calibrated broadband ray tracing for the simulation of wave propagation in mm and sub-mm wave indoor communication channels," in *European Wireless 2012*; 18th European Wireless Conf. 2012. VDE, 2012, pp. 1–10.
- [151] S. Priebe, M. Kannicht, M. Jacob, and T. Kürner, "Ultra broadband indoor channel measurements and calibrated ray tracing propagation modeling at THz frequencies," *Journal of Communications and Networks*, vol. 15, no. 6, pp. 547–558, 2013.
- [152] A. Moldovan, M. A. Ruder, I. F. Akyildiz, and W. H. Gerstacker, "LOS and NLOS channel modeling for terahertz wireless communication with scattered rays," in 2014 IEEE GC Wkshps, Dec. 2014, pp. 388– 392.
- [153] F. Sheikh, N. Zarifeh, and T. Kaiser, "Terahertz band: Channel modelling for short-range wireless communications in the spectral windows," *IET Microwaves, Antennas & Propagation*, vol. 10, no. 13, pp. 1435–1444, 2016.
- [154] B. Peng, S. Rey, and T. Kürner, "Channel characteristics study for future indoor millimeter and submillimeter wireless communications," in 2016 IEEE EuCAP, Apr. 2016, pp. 1–5.
- [155] S. Kim, "THz device-to-device communications: Channel measurements, modelling, simulation, and antenna design," Ph.D. dissertation, Georgia Institute of Technology, 2016.
- [156] S. Priebe and T. Kurner, "Stochastic modeling of THz indoor radio channels," *IEEE Trans. Commun.*, vol. 12, no. 9, pp. 4445–4455, Sep. 2013.
- [157] S. Kim and A. Zajić, "Statistical modeling of THz scatter channels," in 2015 IEEE EuCAP, May 2015, pp. 1–5.
- [158] —, "Statistical modeling and simulation of short-range device-todevice communication channels at sub-THz frequencies," *IEEE Trans. Commun.*, vol. 15, no. 9, pp. 6423–6433, Sep. 2016.
- [159] A. A. Saleh and R. Valenzuela, "A statistical model for indoor multipath propagation," *IEEE J. Sel. Areas Commun.*, vol. 5, no. 2, pp. 128–137, 1987.
- [160] C.-C. Chong, C.-M. Tan, D. I. Laurenson, S. McLaughlin, M. A. Beach, and A. R. Nix, "A new statistical wideband spatio-temporal channel model for 5-GHz band WLAN systems," *IEEE J. Sel. Areas Commun.*, vol. 21, no. 2, pp. 139–150, 2003.
- [161] S. Priebe, M. Jacob, and T. Kuerner, "AoA, AoD and ToA characteristics of scattered multipath clusters for THz indoor channel modeling," in Wireless Conf. 2011-Sustainable Wireless Technologies (European Wireless), 11th European. VDE, 2011, pp. 1–9.
- [162] Y. Choi, "Performance analysis of submillimeter-wave indoor communications using blocking probability," J. Infrared Millim. Terahertz Waves, vol. 36, no. 11, pp. 1123–1136, 2015.
- [163] D. He, K. Guan, A. Fricke, B. Ai, R. He, Z. Zhong, A. Kasamatsu, I. Hosako, and T. Kürner, "Stochastic channel modeling for kiosk applications in the terahertz band," *IEEE Trans. THz Sci. and Technol.*, 2017.
- [164] B. Peng and T. Kürner, "A stochastic channel model for future wireless THz data centers," in *International Symposium on Wireless Communication Systems (ISWCS)*. IEEE, 2015, pp. 741–745.
- [165] A. R. Ekti, A. Boyaci, A. Alparslan, I. Ünal, S. Yarkan, A. Görçin, H. Arslan, and M. Uysal, "Statistical modeling of propagation channels for terahertz band," in 2017 IEEE CSCN, Sep. 2017, pp. 275–280.
- [166] J. Ma, R. Shrestha, L. Moeller, and D. M. Mittleman, "Invited article: Channel performance for indoor and outdoor terahertz wireless links," *APL Photonics*, vol. 3, no. 5, p. 051601, 2018.
- [167] J. F. Federici, J. Ma, and L. Moeller, "Review of weather impact on outdoor terahertz wireless communication links," *Nano Communication Networks*, vol. 10, pp. 13–26, 2016.
- [168] S. Priebe, D. M. Britz, M. Jacob, S. Sarkozy, K. M. Leong, J. E. Logan, B. S. Gorospe, and T. Kurner, "Interference investigations of active communications and passive earth exploration services in the thz frequency range," *IEEE Trans.THz Sci. and Technol.*, vol. 2, no. 5, pp. 525–537, 2012.
- [169] B. Heile, "ITU-R liaison request RE: active services in the band above 275 GHz," *IEEE 802.15-14-439-00-0thz*, July 2015. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group= 0thz

- [170] A. Rogalski and F. Sizov, "Terahertz detectors and focal plane arrays," Opto-Electron. Rev., vol. 19, no. 3, pp. 346–404, 2011.
- [171] J. Kokkoniemi, J. Lehtomäki, and M. Juntti, "Stochastic geometry analysis for mean interference power and outage probability in THz networks," *IEEE Trans. Wireless Commun.*, vol. 16, no. 5, pp. 3017– 3028, 2017.
- [172] K. Tsujimura, K. Umebayashi, J. Kokkoniemi, J. Lehtomäki, and Y. Suzuki, "A causal channel model for the terahertz band," *IEEE Trans. THz Sci. and Technol*, vol. 8, no. 1, pp. 52–62, 2017.
- [173] Y. Chen and C. Han, "Channel modeling and analysis for wireless networks-on-chip communications in the millimeter wave and terahertz bands," in *IEEE International Conf. on Computer Communications Workshops (INFOCOM WKSHPS)*. IEEE, 2018.
- [174] H. Zhao, L. Wei, M. Jarrahi, and G. Pottie, "Extending spatial and temporal characterization of indoor wireless channels from 350 GHz to 650 GHz," *IEEE Trans. THz Sci. and Technol*, 2019.
- [175] I. F. Akyildiz and J. M. Jornet, "Electromagnetic wireless nanosensor networks," *Nano Communication Networks*, vol. 1, no. 1, pp. 3–19, 2010.
- [176] M. A. Khalighi and M. Uysal, "Survey on free space optical communication: A communication theory perspective," *IEEE Commun. Surveys Tuts.*, vol. 16, no. 4, pp. 2231–2258, 2014.
- [177] S. Rangan, T. S. Rappaport, and E. Erkip, "Millimeter-wave cellular wireless networks: Potentials and challenges," *Proceedings of the IEEE*, vol. 102, no. 3, pp. 366–385, 2014.
- [178] J. Ma, "Terahertz wireless communication through atmospheric turbulence and rain," Ph.D. dissertation, New Jersey Institute of Technology, 2016.
- [179] M. Uysal and H. Nouri, "Optical wireless communications- an emerging technology," in 16th International Conf. on Transparent Optical Networks (ICTON). IEEE, 2014, pp. 1–7.
- [180] J. M. Kahn and J. R. Barry, "Wireless infrared communications," *Proceedings of the IEEE*, vol. 85, no. 2, pp. 265–298, 1997.
- [181] J. J. Fernandes, P. A. Watson, and J. C. Neves, "Wireless LANs: physical properties of infra-red systems vs. mmw systems," *IEEE Commun. Mag.*, vol. 32, no. 8, pp. 68–73, 1994.
- [182] S. Arnon, Visible light communication. Cambridge University Press, 2015.
- [183] P. H. Pathak, X. Feng, P. Hu, and P. Mohapatra, "Visible light communication, networking, and sensing: A survey, potential and challenges," *IEEE Commun. Surveys Tuts.*
- [184] Z. Wang, T. Mao, and Q. Wang, "Optical OFDM for visible light communications," in 13th International Wireless Communications and Mobile Computing Conf. (IWCMC). IEEE, 2017, pp. 1190–1194.
- [185] Z. Xu and B. M. Sadler, "Ultraviolet communications: potential and state-of-the-art," *IEEE Commun. Mag.*, vol. 46, no. 5, 2008.
- [186] E. Pickwell and V. Wallace, "Biomedical applications of terahertz technology," *Journal of Physics D: Applied Physics*, vol. 39, no. 17, p. R301, 2006.
- [187] A.-A. A. Boulogeorgos, A. Alexiou, T. Merkle, C. Schubert, R. Elschner, A. Katsiotis, P. Stavrianos, D. Kritharidis, P.-K. Chartsias, J. Kokkoniemi *et al.*, "Terahertz technologies to deliver optical network quality of experience in wireless systems beyond 5G," *IEEE Commun. Mag.*, vol. 56, no. 6, pp. 144–151, 2018.
- [188] I. F. Akyildiz and J. M. Jornet, "The internet of nano-things," *IEEE Wireless Communications*, vol. 17, no. 6, 2010.
- [189] T. Kürner, "What's next? wireless communication beyond 60 GHz (Tutorial IG THz)," *IEEE 802.15-08-0060-02-0thz*, July 2012. [Online]. Available: https://mentor.ieee.org/802.15/dcn/12/ 15-12-0320-01-0thz-what-s-next-wireless-communication-beyond-60-ghz-tutorial-ig pdf
- [190] J. M. Jornet and I. F. Akyildiz, "The internet of multimedia nanothings," *Nano Communication Networks*, vol. 3, no. 4, pp. 242–251, 2012.
- [191] J. F. Federici, B. Schulkin, F. Huang, D. Gary, R. Barat, F. Oliveira, and D. Zimdars, "THz imaging and sensing for security applicationsexplosives, weapons and drugs," *Semiconductor Science and Technol*ogy, vol. 20, no. 7, p. S266, 2005.
- [192] D. F. Plusquellic and E. J. Heilweil, "Terahertz spectroscopy of biomolecules," in *Terahertz Spectroscopy*. CRC Press, 2007, pp. 293– 322.
- [193] K. Yang, Y. Hao, A. Alomainy, Q. H. Abbasi, and K. Qaraqe, "Channel modelling of human tissues at terahertz band," in *Wireless Communications and Networking Conf. Workshops (WCNCW)*. IEEE, 2016, pp. 218–221.

- [194] M. Nafari and J. M. Jornet, "Metallic plasmonic nano-antenna for wireless optical communication in intra-body nanonetworks," in *Proceedings of the 10th EAI International Conf. on Body Area Networks.* ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering), 2015, pp. 287–293.
- [195] P. Biagioni, J.-S. Huang, and B. Hecht, "Nanoantennas for visible and infrared radiation," *Reports on Progress in Physics*, vol. 75, no. 2, p. 024402, 2012.
- [196] H. Elayan, R. M. Shubair, J. M. Jornet, and P. Johari, "Terahertz channel model and link budget analysis for intrabody nanoscale communication," *IEEE Trans. Nanobiosci.*, vol. 16, no. 6, pp. 491–503, 2017.
- [197] H. Elayan, P. Johari, R. M. Shubair, and J. M. Jornet, "Photothermal modeling and analysis of intrabody terahertz nanoscale communication," *IEEE Trans. Nanobiosci.*, vol. 16, no. 8, pp. 755–763, 2017.
- [198] H. Elayan, C. Stefanini, R. M. Shubair, and J. M. Jornet, "End-to-end noise model for intra-body terahertz nanoscale communication," *IEEE Trans. Nanobiosci.*, vol. 17, no. 4, pp. 464–473, 2018.
- [199] K. Nallappan, H. Guerboukha, C. Nerguizian, and M. Skorobogatiy, "Live streaming of uncompressed 4K video using terahertz wireless links," in 2018 IEEE International Conf. on Communications (ICC), May 2018, pp. 1–7.
- [200] Y. Miki, T. Sakiyama, K. Ichikawa, M. Abe, S. Mitsuhashi, M. Miyazaki, A. Hanada, K. Takizawa, I. Masuhara, and K. Mitani, "Ready for 8K UHDTV broadcasting in Japan," in *IBC2015*. IET, 2015.
- [201] T. Kürner, G. Ke, A. F. Molisch, A. Bo, H. Ruisi, L. Guangkai, T. Li, D. Jianwu, and Z. Zhangdui, "Millimeter wave and THz propagation channel modeling for high-data rate railway connectivity-status and open challenges," *ZTE Commun.*, vol. 14, no. S1, p. 1, 2016.
- [202] T. Kürner, "Requirements on wireless backhauling and [225] fronthauling," *IEEE 802.15-08-0336-00-0thz*, November 2013. [Online]. Available: https://mentor.ieee.org/802.15/dcn/13/ 15-13-0636-01-0thz-requirements-for-wireless-backhauling-fronthauling. [226] pdf
- [203] T. Narytnyk, "Possibilities of using THz-band radio communication channels for super high-rate backhaul," *Telecommunications and Radio Engineering*, vol. 73, no. 15, 2014.
- [204] Y. Cui, H. Wang, X. Cheng, and B. Chen, "Wireless data center networking," *IEEE Commun. Mag.*, vol. 18, no. 6, pp. 46–53, Dec. 2011.
- [205] D. Halperin, S. Kandula, J. Padhye, P. Bahl, and D. Wetherall, "Augmenting data center networks with multi-gigabit wireless links," in ACM SIGCOMM Comput. Commun. Rev., vol. 41, no. 4. ACM, 2011, pp. 38–49.
- [206] S. Mollahasani and E. Onur, "Evaluation of terahertz channel in data centers," in 2016 IEEE/IFIP NOMS, Apr. 2016, pp. 727–730.
- [207] R. Roberts, "Link budget exploration for THz communications," *IEEE 802.15-08-0107-00-0thz*, Mar. 2008. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [208] L. Razoumov and D. Britz, "Feasibility of Giga bps data rates at THz frequencies. shannon based link budget analysis," *IEEE 802.15-08-0133-00-0thz*, Mar. 2008. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [209] T. Kürner, "Terahertz communication," IEEE 802.15-08-0336-00-0thz, May 2008. [Online]. Available: https://mentor.ieee.org/802.15/ documents??&\$is\$_\$group=0thz
- [210] J.-S. Rieh, "Current status of semiconductor technologies and circuits for THz applications," *IEEE 802.15-08-0437-00-0thz*, Jul. 2008. [Online]. Available: https://mentor.ieee.org/802.15/documents\$? &sis\$_\$group=0thz
- [211] G. T. Mearini, "High power miniature CVD diamond-based submillimeter/Terahertz signal sources," *IEEE 802.15-08-0741-00-0thz*, Oct. 2008. [Online]. Available: https://mentor.ieee.org/802.15/ documents\$?&\$is\$_\$group=0thz
- [212] R. W. Ridgway, "Millimeter-wave photonics for high data rate wireless communication systems," *IEEE 802.15-08-0433-00-0thz*, Jul. 2008. [Online]. Available: https://mentor.ieee.org/802.15/documents\$? &sis\$_\$group=0thz
- [213] J. Liu, "Integrated photonics for THz applications," IEEE 802.15-08-0746-01-0thz, Nov. 2008. [Online]. Available: https://mentor.ieee.org/ 802.15/documents\$?&\$is\$_\$group=0thz
- [214] R. Roberts, "Some thz system issues," IEEE 802.15-08-0410-01-0thz, Jul. 2008. [Online]. Available: https://mentor.ieee.org/802.15/ documents??&\$is\$_\$group=0thz

- [215] —, "Some THz system issues-part 2-safety," IEEE 802.15-08-0744-00-0thz, Nov. 2008. [Online]. Available: https://mentor.ieee.org/802. 15/documents\$?&\$is\$_\$group=0thz
- [216] T. Kürner, "Scope and work plan of the science committee on THz communications," *IEEE 802.15-09-0229-00-0thz*, Mar. 2009. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group= 0thz
- [217] —, "Towards wireless 100 Gb/s beyond 300 GHz," IEEE 802.15-10-0847-01-0thz, Nov. 2010. [Online]. Available: https: //mentor.ieee.org/802.15/documents??&\$is\$_\$group=0thz
- [218] —, "Update on the Status of WRC 2012 Preparation," *IEEE 80215-11-0462-00-0thz*, Mar. 2011. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [219] I. Hosako, "The road map of THz wireless communications systems for Japan," *IEEE 802.15-11-0491-00-0thz*, Mar. 2011. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [220] R. Roberts, "Some Expectations for THz," *IEEE 802.15-11-0498-00-0thz*, Mar. 2011. [Online]. Available: https://mentor.ieee.org/802.15/ documents\$?&\$is\$_\$group=0thz
- [221] T. Kürner, "Review of the results of WRC 2012," IEEE 802.15-11-0498-00-0thz, Mar. 2012. [Online]. Available: https://mentor.ieee.org/ 802.15/documents\$?&\$is\$_\$group=0thz
- [222] S. Priebe, "Will THz communication interfere with passive remote sensing," *IEEE 802.15-11-0498-00-0thz*, Mar. 2012. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [223] T. Kürner, "On the future of the IG THz," *IEEE 802.15-11-0498-00-0thz*, Mar. 2012. [Online]. Available: https://mentor.ieee.org/802.15/ documents\$?&\$is\$_\$group=0thz
- [224] S. Priebe, "MAC layer concepts for THz communications," *IEEE* 802.15-15-13-0119-00-0thz, Mar. 2013. [Online]. Available: https: //mentor.ieee.org/802.15/documents??&\$is\$_\$group=0thz
- [225] S. Rey, "Link level simulations of THz-communications," IEEE 802.15-15-13-406-00-0thz, Jul. 2013. [Online]. Available: https: //mentor.ieee.org/802.15/documents??&\$is\$_\$group=0thz
- [226] T. Kürner, "Literature review on requirements for wireless data centers," *IEEE 802.15-15-13-411-00-0thz*, Jul. 2013. [Online]. Available: https://mentor.ieee.org/802.15/documents??&\$is\$_\$group=0thz
- [227] A. Kasamatsu, N. Sekine, H. Ogawa, N. Shibagaki, and H. Hanyu, "Optical interconnection of data center," *IEEE 802.15-15-0181-00-0thz*, Mar. 2013. [Online]. Available: https://mentor.ieee.org/802.15/ documents??&\$is\$_\$group=0thz
- [228] C. Yunlong, "THz bridge for data center," IEEE 802.15-15-13-425-00-0thz, Jul. 20132. [Online]. Available: https://mentor.ieee.org/802. 15/documents??&\$is\$_\$group=0thz
- [229] T. Kürner, "On the Scope of IEEE 802.15 SG 100G," IEEE 802.15-13-0635-01-0thz, Nov. 2013. [Online]. Available: https: //mentor.ieee.org/802.15/documents??&\$is\$_\$group=0thz
- [230] —, "Inuaguration of IEEE 802.15 SG 100G," *IEEE 802.15-13-524-03-0thz*, Sept. 2013. [Online]. Available: https://mentor.ieee.org/802.15/documents\$?&\$is\$_\$group=0thz
- [231] —, "TG3d (100G) May 2014 Minutes," IEEE 802.15-14-439-00-0thz, July 2014. [Online]. Available: https://mentor.ieee.org/802.15/ documents\$?&\$is\$_\$group=0thz
- [232] S. Rey, "Progress in regulation above 275 GHz," IEEE 802.15-14-439-00-0thz, July 2016. [Online]. Available: https://mentor.ieee.org/ 802.15/documents\$?&\$is\$_\$group=0thz
- [233] E. G. Larsson, O. Edfors, F. Tufvesson, and T. L. Marzetta, "Massive MIMO for next generation wireless systems," *IEEE Commun. Mag.*, vol. 52, no. 2, pp. 186–195, 2014.
- [234] I. F. Akyildiz and J. M. Jornet, "Realizing ultra-massive MIMO (1024× 1024) communication in the (0.06–10) terahertz band," *Nano Comm. Net.*, vol. 8, pp. 46–54, 2016.
- [235] L. M. Zakrajsek, D. A. Pados, and J. M. Jornet, "Design and performance analysis of ultra-massive multi-carrier multiple input multiple output communications in the terahertz band," in *Proc. of SPIE, Image Sens. Technol.: Materials, Devices, Systems, and Applications IV*, vol. 10209. International Society for Optics and Photonics, 2017, pp. 102 090A1–102 090A11.
- [236] C. Han, J. M. Jornet, and I. Akyildiz, "Ultra-massive mimo channel modeling for graphene-enabled terahertz-band communications," in 87th Vehicular Technology Conf. (VTC Spring). IEEE, 2018, pp. 1–5.
- [237] S. Rodrigo Muñoz, "Multi-user ultra-massive MIMO for very high frequency bands (mmWave and THz): a resource allocation problem," Master's thesis, Universitat Politècnica de Catalunya, 2018.
- [238] "Terahertz-band Ultra-Massive spatial modulation MIMO, author=Sarieddeen, Hadi and Alouini, Mohamed-Slim and Al-Naffouri, Tareq Y, journal=arXiv preprint arXiv:1905.04732, year=2019."

- (2017) [239] ABI Research. Augmented and virtual real-5G itv: the first wave of killer apps. [On-Available: https://www.gualcomm.com/media/documents/files/ line]. augmented-and-virtual-reality-the-first-wave-of-5g-killer-apps.pdf
- [240] C. Chaccour, R. Amer, B. Zhou, and W. Saad, "On the reliability of wireless virtual reality at Terahertz (THz) frequencies," arXiv preprint arXiv:1905.07656, 2019.
- [241] Z. Li, L. Guan, C. Li, and A. Radwan, "A secure intelligent spectrum control strategy for future THz mobile heterogeneous networks," *IEEE Commun. Mag.*, vol. 56, no. 6, pp. 116–123, 2018.
- [242] M. Giordani, M. Polese, M. Mezzavilla, S. Rangan, and M. Zorzi, "Towards 6G networks: Use cases and technologies," *arXiv preprint* arXiv:1903.12216, 2019.
- [243] Y. Li, Y. Zhang, K. Luo, T. Jiang, Z. Li, and W. Peng, "Ultradense HetNets meet big data: Green frameworks, techniques, and approaches," *IEEE Commun. Mag.*, vol. 56, no. 6, pp. 56–63, 2018.
- [244] G. Alnwaimi, S. Vahid, and K. Moessner, "Dynamic heterogeneous learning games for opportunistic access in LTE-Based macro/femtocell deployments," *IEEE Commun. Lett.*, vol. 14, no. 4, pp. 2294–2308, Apr. 2015.
- [245] X. Cheng, B. Yu, L. Yang, J. Zhang, G. Liu, Y. Wu, and L. Wan, "Communicating in the real world: 3D MIMO," *IEEE Commun. Mag.*, vol. 21, no. 4, pp. 136–144, Aug. 2014.
- [246] H. Halbauer, S. Saur, J. Koppenborg, and C. Hoek, "3D beamforming: Performance improvement for cellular networks," *Bell Labs Tech. J*, vol. 18, no. 2, pp. 37–56, Sep. 2013.
- [247] B. Orazbayev, M. Beruete, and I. Khromova, "Tunable beam steering enabled by graphene metamaterials," *Optics express*, vol. 24, no. 8, pp. 8848–8861, 2016.
- [248] L. You, X. Gao, G. Y. Li, X.-G. Xia, and N. Ma, "BDMA for millimeter-wave/terahertz massive MIMO transmission with per-beam synchronization," *IEEE J. Sel. Areas Commun.*, vol. 35, no. 7, pp. 1550–1563, 2017.
- [249] N. Choubey and A. Panah, "Introducing facebook's new terrestrial connectivity systems-terragraph and project aries," *Facebook Research*, 2016.
- Weissberger. [250] A. J. (2018) ITU-R's role in radio frequency spectrum for 5G networks of the future. Available: https://techblog.comsoc.org/2018/10/24/ [Online]. itu-rs-role-in-radio-frequency-spectrum-for-5g-networks-of-the-future/
- [251] G. Araniti, C. Campolo, M. Condoluci, A. Iera, and A. Molinaro, "Lte for vehicular networking: a survey," *IEEE Commun. Mag.*, vol. 51, no. 5, pp. 148–157, 2013.
- [252] M. Giordani, A. Zanella, and M. Zorzi, "Lte and millimeter waves for v2i communications: an end-to-end performance comparison," arXiv preprint arXiv:1903.04399, 2019.
- [253] N. Lu, N. Cheng, N. Zhang, X. Shen, and J. W. Mark, "Connected vehicles: Solutions and challenges," *IEEE internet of things journal*, vol. 1, no. 4, pp. 289–299, 2014.
- [254] V. Petrov, G. Fodor, J. Kokkoniemi, D. Moltchanov, J. Lehtomaki, S. Andreev, Y. Koucheryavy, M. Juntti, and M. Valkama, "On unified vehicular communications and radar sensing in millimeter-wave and low terahertz bands," *arXiv preprint arXiv:1901.06980*, 2019.
- [255] K. Guan, B. Peng, D. He, J. M. Eckhardt, S. Rey, B. Ai, Z. Zhong, and T. Kürner, "Measurement, simulation, and characterization of train-toinfrastructure inside-station channel at the terahertz band," *IEEE Trans. THz Sci. and Technol.*, vol. 9, no. 3, pp. 291–306, 2019.
- [256] K. Kanai, T. Muto, J. Katto, S. Yamamura, T. Furutono, T. Saito, H. Mikami, K. Kusachi, T. Tsuda, W. Kameyama *et al.*, "Proactive content caching for mobile video utilizing transportation systems and evaluation through field experiments," *IEEE J. Sel. Areas Commun.*, vol. 34, no. 8, pp. 2102–2114, 2016.
- [257] Y. Zeng, R. Zhang, and T. J. Lim, "Wireless communications with unmanned aerial vehicles: opportunities and challenges," *IEEE Commun. Mag.*, vol. 54, no. 5, pp. 36–42, May 2016.
- [258] S. Mumtaz, J. M. Jornet, J. Aulin, W. H. Gerstacker, X. Dong, and B. Ai, "Terahertz communication for vehicular networks," *IEEE Trans. Veh. Technol.*, vol. 66, no. 7, pp. 5617–5625, 2017.
- [259] J. Ma, R. Shrestha, J. Adelberg, C.-Y. Yeh, Z. Hossain, E. Knightly, J. M. Jornet, and D. M. Mittleman, "Security and eavesdropping in terahertz wireless links," *Nature*, vol. 563, no. 7729, p. 89, 2018.